



REPAIR MORTAR 45

FLEXURAL COMPRESSIVE TENSILE STRENGTH

FOR PROFESSIONAL USE ONLY

Description: Portland Cement based with fiber enhancement and abrasion resistant additives.

Product Features:

Light weight (106 lbs/cf) Apply as thin as 1/4"
Quick return to service Minimizes propagation of cracks

Tools Required: Large mixing bucket, measuring cup and powerful dual paddle electric mixer.

Shelf Life: 1 year, when stored in a dry area.

Refer to the **TECHNICAL Data SHEET** for Complete Guidelines!

Mixing: Fill a sufficient size bucket with all the mix water, then add 1/2 of the mortar and thoroughly mix, add the remainder of mix, and continue mixing. Mix thoroughly until the mortar has a consistent mixture, scrape the sides of the mixing bucket with a trowel to ensure that all the dry material gets mixed thoroughly. Mix for another 30-60 seconds once the sides of the bucket has been scraped off. **Total mixing water shall be in the range 150 oz – 180 oz per 45 lb.** For optimal mixing, use a dual paddle hand-held mixer such as the BNR6402K or barrel style concrete.
Curing: Water Cure for a minimum of 2 hours after final finishing. Then apply **HMI RM Sealer**. Lab test to follow **AASHTO R39-19**.

DANGER



DO NOT BREATHE DUST, AVOID CONTACT WITH SKIN AND EYES!

Contains: Crystalline Silica CAS#14808-60-7, Calcium Compounds CAS#65997-15-1, Glass Granules, Gypsum CAS#13397-24-5

Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. May cause cancer by inhalation. May cause respiratory irritation.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.



WARNING

This product contains Crystalline Silica and chemicals (trace metals) known to the State of California to cause cancer, birth defects or other reproductive harm.

For more information go to:
www.P65Warnings.ca.gov

IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower]. Wash contaminated clothing before reuse. IF SKIN irritation or rash occurs: Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment (see SDS).

Emergency Telephone Number (U.S.):
INFOTRAC 1-800-535-5053

Emergency Telephone Number (International):
1-352-323-3500

SDS available upon request

KEEP THIS PRODUCT OUT OF THE REACH OF CHILDREN



6012 Windsor Dr.
Milan, TN 38358
731-238-3109

Made in the USA

45 lbs. (20.41 KG)