



RM PRIMER

[HMI Repair Mortar Primer] is a bonding adhesive primer for use with all HMI repair mortar products.

MADE IN THE USA

PREPARATION: Surfaces to which HMI Repair Mortar Primer is to be applied must be clean, structurally sound, free of standing water or contaminants. Pre-dampen clean surfaces before application.

COVERAGE: HMI Repair Mortar Primer has a mix ratio of 2 gallons per 45lb bag of HMI repair mortar. Coverage is 60 sq. ft.

SLURRY/BOND COAT: Blend HMI Mortar with enough undiluted HMI Repair Mortar Primer to make a paint - like consistency. Work slurry into the repair area or substrate with a stiff masonry brush coating the entire area. Pay special attention to the corners, sides and any exposed rebar. Place HMI Mortar prior to the slurry coat becoming tack-free.

BONDING AGENT: HMI Repair Mortar Primer undiluted by brush, roller or pump sprayer on to the prepared surface. When the primed surface begins to turn blue/green, place the HMI Mortar before primer dries and becomes tack-free.

WARNING May be harmful if swallowed. Causes mild skin irritation. Causes eye irritation

Wash hands, face and any exposed skin thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. **IF eye irritation persists:** Get medical attention. **IF SKIN irritation occurs:** Get medical attention. Call a **POISON CENTER** or doctor if you feel unwell.

Dispose of container in accordance with local, state, and federal regulations.

For further safety information, please refer to

- ◆ Non-Toxic
- ◆ Non-Flammable
- ◆ Safe
- ◆ Easy To Use

Manufactured by:



6012 Windsor Dr.
Milan, TN 38358
731-238-3109