

## **STANDARD FEATURES**

- LH or RH Operator Controls
- 3 foot platform extension deck on rollers
- Power to Platform
- Foldable guardrails and full height entry gate
- Swing out Battery and Hydraulic trays for easy service and maintenance
- Meets ANSI A92 and CSA B354 Requirements
- 2-year/2,000 hour warranty

282 Hudson Street Hackensack, NJ 07601

201-342-8020 www.berequipment.com





**1**/BER Equipment Rentals ■ Boland\_Equipment\_Rentals

## **JCB ELECTRIC SCISSORS**



www.berequipment.com

201-342-8020

		S1930E	S2632E	S3246E	S4046E
Max. platform height	ft-in (m)	18-9 (5.7)	26-0 (7.92)	31-10 (9.70)	39-0 (11.9)
Max. working height	ft-in (m)	24-9 (7.7)	32-0 (9.92)	37-10 (11.70)	45-0 (13.9)
Length (stowed)	ft-in (m)	5-10 (1.78)	7-10 (2.39)	7-10 (2.39)	7-10 (2.39)
Width (stowed)	ft-in (m)	2-6 (.76)	2-8 (.81)	3-9 (1.15)	3-9 (1.15)
Height (stowed, guardrails folded)	ft-in (m)	6-1 (1.86)	6-5 (1.96)	6-1 (1.86)	6-6 (1.98)
Height (stowed, guardrails unfolded)	ft-in (m)	6-11 (2.12)	7-8 (2.35)	8-2 (2.48)	8-6 (2.6)
Weight	lb (kg)	3,739 (1,696)	4,806 (2,180)	6,318 (2,866)	6,768 (3,070)
Deck extension	ft-in (m)	3-0 (0.9)	3-0 (0.9)	3-0 (0.9)	3-0 (0.9)
Load capacity	lb (kg)	505 (230)	550 (250)	705 (320)	705 (320)
Ground clearance (stowed)	in (cm)	2.75 (7)	4 (10)	4 (10)	4 (10)
Gradeability	%	25	25	25	25
Max. driving speed (stowed)	mph (km/h)	1.7 (2.8)	2 (3.2)	2 (3.2)	2 (3.2)
Max. driving speed (raised)	mph (km/h)	0.5 (0.8)	0.5 (0.8)	0.5 (0.8)	0.5 (0.8)





## THE JCB CONSTRUCTION RANGE

**COMPACT EXCAVATORS** 





TELESCOPIC HANDLERS
-LIFT & PLACE



**TELETRUKS** 



TELESCOPIC HANDLERS
-TOOL CARRIER



WHEEL LOADERS



WHEELED EXCAVATORS



TELESKIDS



TRACKED EXCAVATORS



SKID STEER AND COMPACT TRACK LOADERS



**ELECTRIC SCISSORS** 



BACKHOE LOADERS