



3232SE^{AC} Electric Slim Scissor Lift

- Drives at Full Height Indoors Saving Time and Battery Energy Between Overhead Tasks
- Greater Productivity Due to Outrigger-Free Design
- AC Electric Drive for Extended Duty Cycles, Smoother Controls and Faster Drive Speeds
- Compact Maneuverability from Front Wheel Drive and Steer with Zero Inside Turn Radius
- Fully Proportional Lift and Drive Controls
- Standard Swing Gate
- Easy Serviceability with Swing Out Battery and Power Module Trays
- Maintenance-Free AGM Batteries



201-342-8020
www.berequipment.com

282 Hudson Street
Hackensack, NJ 07601

Do More Work by Driving Elevated Between Overhead Tasks up to 38 ft.

Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions
 Standard Swing Gate
 Lanyard Attachments (4)

Performance

Drive at Full Height Indoors
 No Outriggers
 AC Electric Drive
 Fully Proportional Drive and Lift Controls
 Up to 25% Gradeability

Power

Maintenance-Free AGM Batteries
 Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
 Easy Maintenance Access to Mechanical and Electrical Components
 in a Slide-Out Tray
 Logically Grouped Components and Numbered Wiring for Easy Reference

Safety

Dedicated Compartment Protects Electrical and Hydraulic Components
 Emergency Shut-Off at Platform and Lower Controls
 Non-Skid Metal Deck Construction
 Descent Alarm
 Drive Speed Interlock
 Multi-Axis Tilt Sensor
 Scissor Maintenance Lock
 Multiple Disc Brakes

Other Features

Removable Upper Controls	Machine Tie Downs
Voltage-Compensating Fully Automatic Battery Charger	Non-Marking Tires
Fold-Down Guardrails	All Motion Alarm
Hour Meter	Fork Lift Pocket
	Flashing Beacon (Continuous)

Optional Features

Leak Containment System® (LCS) Patent #11,112,060	Proactive Platform Safety System® (PPSS)
900W Inverter	Upper Control Box Supplementary Guard Pipe Rack
Tool Tray	Second Year Extended Warranty
Cold Weather Package	



MEC Aerial Work Platforms



www.berequipment.com

MEC®, Leak Containment System® & Proactive Platform Safety System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® Patent #11,112,060.

3232SE ^{AG}	U.S.	Metric
Heights		
Indoor Working Height*	38 ft.*	11.6 m*
Outdoor Working Height*	30 ft.*	9.1 m*
Indoor Platform Height	32 ft.	9.8 m
Outdoor Platform Height	24 ft.	7.3 m
Stowed Height (Top Guardrail)	96 in.	2.4 m
Stowed Height (Rails Folded)	78 in.	2 m
Stowed Height (Platform Floor)	53 in.	1.3 m
Guardrail Height	43.5 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	4 in.	10 cm
Ground Clearance (Elevated)	.7 in.	2 cm
Dimensions		
Length-Stowed (Overall)	97 in.	2.5 m
Length-Stowed (Ladder Removed)	89.5 in.	2.3 m
Chassis Width	32 in.	81 cm
Platform Length (Extended)	124.5 in.	3.2 m
Platform Length (Retracted)	89.5 in.	2.27 m
Roll-Out Deck Length	35 in.	90 cm
Platform Width	32 in.	81 cm
Wheelbase	74 in.	1.9 m
Total Lift Capacity	550 lbs	250 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs	113 kg
Speed		
Raise/Lower Speed	52 s / 38 s	
Drive Speed (Stowed)	3 mph	5 km/h
Drive Speed (Elevated)	0.5 mph	0.8 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	0 in.	0 m
Weight**	6,945 lbs.	3,150 kg
Power Source	24v 240Ah Maintenance-Free Batteries	
Controls	Proportional Drive & Lift Controls	
Tires	15 x 5 in.	38 x 13 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 **Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6 - 2017.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

