



COATINGS SOLUTIONS

HIGH PERFORMANCE

www.coatingsoln.com - Office: 863-398-4619 E-mail: info@coatingsoln.com

Technical Data Sheet

3928 Anchuca Drive STE20

Lakeland, FL 33811

Fast Strip

DESCRIPTION:

Fast Strip is a high effective industrial coating, sealer and adhesive remover. It's based on a strong emulsifier won't dry out like other strippers.

ADVANTAGES:

- Removes multiple layers in one application
- Effective on acrylics, wb epoxies & enamels
- Strong emulsifier package lifts sealer in 15-20 min
- Water soluble clean rinse technology
- Spray-able
- Algae and mold Inhibitor
- Inhibits weed growth
- VOC compliant <100 g/L
- Methylene chloride and caustic free
- Not Flammable

PHYSICAL PROPERTIES:

Appearance	Slight haze
Viscosity	500-800 cps
Odor	Citrus Fragrance
Specific Gravity	1.13

COVERAGE:

200 to 500 sq. ft. per gallon

MIXING:

Invert can few times to mix contents.

APPLICATION

Pour contents into a pump-up sprayer system, cover and or dampen with water any grass or plants and flowers they may come into contact with stripper over spray. Then uniformly apply a flood coat Fast Strip. Hold sprayer tip 12" from the surface. Let sit 15-20 minutes until sealer starts to turn grayish or shows signs of peeling. Using a plastic putty knife should be able to scrap failed sealer from the substrate. At this point ready to rinse using a pressure washer. Use a fan tip as zero tip will leave spray lines the substrate. Can also be applied using a ½ nap roller.

CLEANUP:

Immediately flush sprayer pump with water. Repeat this step at least two times. Always flush system again morning before spraying ensure its not restricted.

STORAGE:

Store at temps above 50F. If product freezes, it is no longer usable. Shelf life is 2 years.

SHIPPING:

Ships DOT Non-Flammable, Non-Hazardous.

WARRANTY:

Materials are free of defect. No labor

