

DATA SHEET

E-Vapz™

Evaporation Reducer For Plastic Concrete

Concord Sealers, Inc.

60 Centenary Place, Logan Village, QLD, 4207
Phone: 07 5547 0052
Website: www.concordsealers.com

PRODUCT DESCRIPTION

E-Vapz is a concentrated, odorless, water-based polymer liquid that, when placed on fresh concrete, forms a thin, continuous monomolecular film that temporarily reduces rapid moisture loss from the concrete surface. **E-Vapz** reduces contractor field problems with exposed exterior concrete by minimizing surface crusting and plastic shrinkage cracks.

E-Vapz helps achieve superior quality flatwork. It minimizes early water evaporation and controls the surface condition of the slab to aid in meeting finishing schedules. It is effective in minimizing rapid drying conditions due to high temperatures, low humidity, high winds and direct sunlight.

Basic Use: **E-Vapz** forms a temporary, protective film on plastic concrete surfaces that prevents rapid moisture loss. The protective shield formed usually lasts as long as the concrete remains plastic, despite successive floating and troweling operations. No residue remains after the concrete hardens.

Use **E-Vapz** evaporation control to assist with standard concrete mixes, silica fume concrete, thin concrete resurfacing, and all cementitious shake on floor hardeners after placement.

FEATURES & BENEFITS

- Reduces plastic shrinkage cracks.
- Reduces evaporation rates up to 80% in wind and 40% in hot sunlight.
- Minimizes surface crusting
- Cement hydration is improved.
- Improves durability by controlling evaporation.

- Remains effective after screeding and first floating operation.
- Non-residual.
- Economically concentrated

ESTIMATING

E-Vapz is available in 5 litre, 20 litre, 200 litre and 1000 litre containers. Each container is clearly identified with product name and batch number.

Dilution Rate - 10 parts water: 1 part **E-Vapz**

Coverage 5 - 10 m²/liter after dilution.

TECHNICAL DATA

Standards- ACI-305R

- Color – pink
- VOC compliant.

INSTALLATION

Mixing: Shake or mix concentrate before dilution. Add 10 parts of water to 1 part **E-Vapz** Concentrate. Mix or shake until thoroughly blended.

Application: Use clean, dry spray equipment with fogging tips. Spray immediately after bull floating and during finishing operation as needed. In extreme drying conditions, re-apply additional material as needed. Use on fresh plastic concrete, as well as between shake-on hardener applications. Apply lightly to hard-to-trowel floor areas. Do not puddle. Concrete plastic shrinkage cracks and resulting stress cracks are a strong possibility when the rate of evaporation exceeds 1.0 kg/m²/hour.

Evaporation rate is a direct function of relative humidity, concrete temperature, air temperature, and wind velocity. The use of **E-Vapz** is concrete approaches or exceeds this level.

recommended when the rate of evaporation of the concrete approaches or exceeds this level.

ACI Committee 305, "Recommended Practice for Hot Weather Concreting," developed a chart, which graphically determines evaporation rates under a given set of job site conditions.

FOR BEST RESULTS

- Do not use concentrated
- Use at proper dilution rate
- Do not use as a curing compound
- Apply only as fine spray
- Avoid puddling
- Immediately wipe up any wet residue from hardened concrete surfaces and rinse surface to avoid stains.
- Clean up with soap and water.
- Do not allow to freeze.

PRECAUTIONS

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not take internally. Wear skin and eye protection.

Please refer to Product Safety Data Sheet (SDS) before using.

STORAGE/SHELF LIFE

E-Vapz containers are to be kept tightly sealed and stored in a cool, dry place. Shelf life is one year when stored properly, between -
Keep from freezing.

SHORT SPEC:

033000: Evaporation control: Apply mono molecular film to fresh plastic concrete one or more times as needed, before and after finishing operation (ACI 305R).

WEBSITE:

Concord Sealers convenient Internet website offers instant access to Tech Data Sheets, Material Safety Data Sheets, product updates, and other useful information. Visit www.concordsealers.com and follow the easy steps. Concord Sealers is ready to respond to your concrete information needs - anytime - anywhere!

LIMITED WARRANTY

This product is warranted to be free of defects in material and workmanship and conform to Concord Sealers Construction Chemical quality control standards. All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty or guaranty of

any kind, expressed or implied including but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose. Satisfactory results depend upon many factors beyond Concord Sealers' control. Users shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk, loss, damage, expense and liability resulting from his or her direct use, indirect use or consequential to their use of the product. Concord Sealers shall not be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use or inability to use the product. Concord Sealers' sole responsibility shall be to replace that portion of the product which proves to be defective. Any warranty claim must be made within six (6) months of the date of the claimed breach. This limited warranty applies only if the product was properly installed and used according to all instructions and was properly stored prior to use.

For Professional Use Only.

©2023 Concord Sealers, Inc.

