

# US WATERMAKER

## Skid Mounting Options Available

### Example Skids



TOTAL CAPACITY  
10,000 GPD

TOTAL CAPACITY  
6,000 GPD



TOTAL CAPACITY  
1,200 GPD



**USWATERMAKER** systems are built utilizing high quality materials to ensure long life in the rough seawater environment. They are designed for 24/7 commercial duty, ease of operation and maintenance with accessibility that is second to none.

# SKID MOUNTING

USWATERMAKER, INC.

Production Capacity (GPD)	500 to 10,000 GPD
Raw Water Flow	4.2 to 14.8 GPM
Pre-filter	Commercial 5 & 25 Micron, Glass Media Filter
Motor TEFC Close Coupled	3 HP or 5 HP
Phase	Single or Three Phase
Volts	230 (Single Phase) 208, 230 or 460 (Three Phase)
Frame Dimensions	63" High x 72" Wide x 32" Deep(10,000 GPD)
High Pressure Pump	CAT PUMPS®3CP or 5CP, 316 Stainless Steel Pump Head
High Pressure Control	Adjustable Pressure Regulator and Safety Switch
Low Pressure Control	Low Pressure Safety Switch
Pressure Vessels	Composite
Membranes	Seawater 2540 or 4040
Operating Pressures	850 PSI
Feed Pump	Ampco NAB Centrifugal Pump
Feed Pressure	2 PSI Minimum

US Watermaker, Inc.  
Sales Manager Tom Shrader  
Phone (713) 503-3852  
[tom.shrader@uswatermaker.com](mailto:tom.shrader@uswatermaker.com)