

# US WATERMAKER

## Skid Mounting Options Available

### Example Skids



TOTAL CAPACITY  
10,000 GPD

TOTAL CAPACITY  
6,000 GPD



TOTAL CAPACITY  
1,200 GPD



**USWATERMAKER** systems are built utilizing high quality materials to ensure long life in the rough seawater environment. They are designed for 24/7 commercial duty, ease of operation and maintenance with accessibility that is second to none.

|                           |   |
|---------------------------|---|
| Production Capacity (GPD) | 500 to 10,000 GPD                                   |
| Raw Water Flow            | 4.2 to 14.8 GPM                                     |
| Pre-filter                | Commercial 5 & 25 Micron, Glass Media Filter        |
| Motor TEFC Close Coupled  | 3 HP or 5 HP  |
| Phase                     | Single or Three Phase                               |
| Volts                     | 230 (Single Phase)<br>208, 230 or 460 (Three Phase) |
| Frame Dimensions          | 63" High x 72" Wide x 32" Deep(10,000 GPD)          |
| High Pressure Pump        | CAT PUMPS®3CP or 5CP, 316 Stainless Steel Pump Head |
| High Pressure Control     | Adjustable Pressure Regulator and Safety Switch     |
| Low Pressure Control      | Low Pressure Safety Switch                          |
| Pressure Vessels          | Composite   |
| Membranes                 | Seawater 2540 or 4040                               |
| Operating Pressures       | 850 PSI   |
| Feed Pump                 | Ampco NAB Centrifugal Pump                          |
| Feed Pressure             | 2 PSI Minimum                                       |

Hydro Dynamics Solutions  
Sales Manager Tom Shrader  
Phone (713) 503-3852  
[tom.shrader@hdsmarine.com](mailto:tom.shrader@hdsmarine.com)