

END-TO-END | Scooter Specifications



MODEL NAME	Quest®	Go-Go®Ultra X	Go-Go®Elite Traveller Plus	Go-Go® LX w/ CTS Suspension	Revo® 2.0	Zero Turn 8	Zero Turn 10	Pathrider® ES 10	Pathrider® 10	Pathrider® 10 DX	Gopher SV	Victory® LX w/ CTS Suspension	Celebrity® DX	Celebrity® XL DX	Pathrider® 130 XL	Pathrider® 140 XL	Outback®	Sport Rider
FRONT TYRES	4 cm x 18 cm (1.5"x 7") solid	3W: 5 cm x 20.3 cm (2"x 8") solid 4W: 5 cm x 17.8 cm (2"x 7") solid	5 cm x 20.3 cm (2"x 8") solid	5 cm x 17.8 cm (2"x 7") solid	6.3 cm x 22.8 cm (2.5"x 9") solid	5 cm x 17.8 cm (2"x 7") solid	22.8 cm x 7 cm (9"x 2.75") solid	9.1 cm x 26.4 cm (3.6"x 10.4")	9 cm x 25.4 cm (3.5"x 10")	9 cm x 25.4 cm (3.5"x 10")	7.62 cm x 25.4 cm (3"x 10")	9 cm x 25.4 cm (3.5"x 10")	9 cm x 25.4 cm (3.5"x 10")	10 cm x 33 cm (4"x 13")	10 cm x 33 cm (4"x 13")	10 cm x 33 cm (4"x 13")	37 cm x 15.2 cm (14.5"x 6")	6.9 cm x 48.2 cm (2.75"x 19") ¹⁷
REAR TYRES	5 cm x 20 cm (1.9"x 7.8") solid	6.35 cm x 20.3 cm (2.5"x 8") solid	7.6 cm x 22.9cm (3"x 9") solid	6.35 cm x 20.3 cm (2.5"x 8") solid	6.3 cm x 22.8 cm (2.5"x 9") solid	6.35 cm x 22.9 cm (2.5"x 9") solid	27.3 cm x 8.25 cm (10.75"x 6") solid	9.1 cm x 27.3 cm (3.6"x 10.75") solid	9 cm x 25.4 cm (3.5"x 10")	10 cm x 25.4 cm (4"x 10")	7.62 cm x 25.4 cm (3"x 10")	9 cm x 25.4 cm (3.5"x 10")	10 cm x 25.4 cm (4"x 10")	10 cm x 25.4 cm (4"x 10")	10 cm x 33 cm (4"x 13")	10 cm x 33 cm (4"x 13")	37 cm x 15.2 cm (14.5"x 6")	6.9 cm x 48.2cm (2.75"x 19") ¹⁷
MAXIMUM SPEED ¹⁸	Up to 6 km/h (3.7 mph)	Up to 6.4 km/h (4 mph)	Up to 7.2 km/h (4.5 mph)	Up to 7 km/h (4.4 mph)	Up to 8 km/h (5 mph)	Up to 6.4 km/h (4 mph)	Up to 10 km/h (6.2 mph)	Up to 8.85 km/h (5.5 mph)	Up to 8.4 km/h (5.25 mph)	Up to 8.85 km/h (5.5 mph)	Up to 10 km/h (6.2 mph)	Up to 9 km/h (5.6 mph)	Up to 9.65 km/h (6 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)	Up to 10 km/h (6.2 mph)
GROUND CLEARANCE ^{4,13,15}	5.8 cm (2.3") at frame	6.3 cm (2.5") at midframe 3.8 cm (1.5") at motor	7.62 cm (3") at frame	6.4 cm (2.5") at frame 3.8 cm (1.5") at motor	8.9 cm (3.5") at frame 3.2 cm (1.25") at motor	8.9 cm (3.5") at frame 3.2 cm (1.3") at motor	5 cm (2") at motor	8.8 cm (3.5") at frame	7.6 cm (3") at midframe	8.25 cm (3.25") at midframe	4 cm (1.5") at rear frame	5.6 cm (2.2") at motor	8.25 cm (3.25")	10.8 cm (4.25")	19.7 cm (3.8")	13.3 cm (5.25") at midframe	14 cm (5.5") at motor	12.7 cm (5") at shroud
TURING RADIUS ⁴	82 cm (32")	3W: 83.8 cm (33") 4W: 112 cm (44")	116.2 cm (45.72")	116.2 cm (45.72")	132.1 cm (52")	97.2 cm (38.25")	109 cm (43")	132 cm (51.9")	137 cm (53.9")	133.3 cm (52.5")	143 cm (56.2")	152 cm (59.9")	3W: 105.4 cm (41.5") 4W: 149.8 cm (59")	168.2 cm (66.2")	170 cm (67")	210 cm (83") right 208 cm (82") left	243 cm (95.6")	3W: 158 cm (62.2")
LENGTH & WIDTH ^{4,12}	92.7 cm/49.5 cm (36.5"/19.5")	3W: 94 cm/49.5 cm (37"/19.5") 4W: 100.3 cm/49.5 cm (39.5"/19.5")	102.3 cm/54 cm (40.25"/21.25")	104 cm/52.1 cm (41"/20.5")	119.4 cm/52.7 cm (47"/20.75")	116 cm/50.8 cm (45.75"/20")	122 cm/61.6 cm (48"/24.25")	115.6 cm/57.1 cm (45.5"/22.5")	115 cm/56.5 cm (45.25"/22.25")	119.4 cm/56.2 cm (47"/22.13")	119 cm/59 cm (46.8"/23.2")	119.4cm/56.5cm (47"/22.25")	3W:116.8 cm/61 cm (46"/24") 4W: 118.7 cm/61 cm (46.75"/24")	130.2 cm/64.1 cm (51.25"/25.25")	136 cm/63.6 cm (53.5"/25")	142.8 cm/69.2 cm (56.25"/27.25")	156 cm/83 cm (61.4"/32.6")	3W: 165 cm/78 cm (65"/30.7")
SEAT-TO-GROUND HEIGHT RANGE	51 cm (20") Fixed	55 cm - 60 cm (21.6"- 23.6")	52 cm - 55.88 cm (20.5"- 22")	52.7 cm - 56.5 cm (20.75"- 22.25")	53.3 cm - 60 cm (21"- 23.5")	53.3 cm - 60 cm (21"- 23.5")	58.4 cm - 63.5 cm (23"- 25")	51.4 cm - 55.2 cm (20.25"- 21.75")	52 cm - 55.8 cm (20.5"- 22")	60cm - 63.8 cm (23.6"- 25.1")	61 cm - 64 cm (24"- 25.2")	60 cm - 64.8 cm (23.5"- 25.5")	58.5 cm - 61.5 cm (23"- 24.25")	54 cm - 64 cm (21.25"- 25.25")	56.7 cm (22.3")	66.7 cm - 70.5 cm (26.25"- 27.75")	76 cm - 80 cm (30"- 31.5")	63 cm (24.8")
SEAT TYPE (STANDARD) ⁶	Compact, Foldable, Molded Plastic 41 cm x 33 cm (16"x 13")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Compact, Foldable, 43 cm x 43 cm (17"x 17")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5"x 17.5")	Foldable Molded Plastic 46 cm x 43 cm (18"x 17")	Foldable Molded Plastic 46 cm x 43 cm (18"x 17")	CRS Junior Seat 44.25 cm x 43 cm (17.5"x 17")	Foldable Molded Plastic 48 cm x 42 cm (19"x 16.5")	Reclining H/B w/ Sliders & Headrest 46 cm x 46 cm (18"x 18")	Deluxe Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18"x 18")	Deluxe Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18"x 18")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5"x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5cm x 44.5cm (19.5"x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5cm x 44.5cm (19.5"x 17.5")	Captains High-Back Adjustable Seat 51cm x 56cm (20"x 22")
WEIGHT ^{3,4,14}	4W: 23.5 kg (51.8 lbs)	3W: 34.5 kg (76 lbs) 4W: 36.3 kg (80 lbs)	4W: 39.4 kg (87 lbs)	4W: 39.4 kg (87 lbs)	4W: 60 kg (132 lbs)	4W: 53.9 kg (119 lbs)	4W: 82.1 kg (180 lbs)	4W: 59.4 kg (130.9 lbs)	4W: 62.4 kg (137.5 lbs)	4W: 84.8 kg (186.9 lbs)	4W: 68.9 kg (151.8 lbs)	4W: 81.2 kg (179 lbs)	3W: 70.7 kg (156 lbs) 4W: 75 kg (165 lbs)	4W: 112 kg (246.9 lbs)	4W: 99.8 kg (220 lbs)	4W: 117.7 kg (259 lbs)	4W: 124 kg (273 lbs)	3W:115 kg (253.5 lbs)
SEAT-TO-DECK HEIGHT RANGE	31 cm (12.2") Fixed	40 cm - 43.8 cm (15.75"- 17.25")	41.3 cm - 45 cm (16.25"- 17.75")	41.3 cm - 43.8 cm (16.25"- 17.25")	38.1 cm - 45.7 cm (15"- 18")	40.6 cm - 45.6 cm (15.9"- 17.9")	47.5 cm - 52.5 cm (18.7"- 20.6")	37cm - 42 cm (14.5"- 16.5")	43.8 cm - 47.6 cm (17.2"- 18.75")	44.5 cm - 48.3 cm (17.5"- 19")	46 cm - 49 cm (18.1"- 19.3")	42 cm - 47 cm (16.5"- 18.5")	41 cm - 44.5 cm (16.2"- 17.5")	43.2 cm - 53.3 cm (17"- 21")	47 cm (18.5")	53.3 cm - 57 cm (21"- 22.5")	50 cm - 53 cm (19.6"- 21")	47.5 cm (18.7")
BATTERY WEIGHT ¹¹	2.3 kg (5 lbs)	4.08 kg (9 lbs) ea ²	6.05 kg (13.3 lbs) ea ²	6.05 kg (13.3 lbs) ea ²	11 kg (24.2 lbs) ea	6.05 kg (13.3 lbs) ea	14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	10.5 kg (23.1 lbs) ea or 14.16 kg (31.2 lbs) ea	14.16 kg (31.2 lbs) ea	16.8 kg (37 lbs) ea	23.45 kg (51.6 lbs) ea	27.9 kg (61.5 lbs) ea	23.75 kg (52.3 lbs) ea
BATTERY REQUIREMENTS ⁷	(1) Lithium 11.5 AH	(2) 12AH	(2) 18AH	(2) 18AH	(2) 31AH	(2) 22AH	(2) 40AH	(2) 31AH	(2) 31AH or (2) 40AH	(2) 31AH or (2) 40AH	(2) 40AH	(2) 40 AH	(2) 31AH or (2) 40AH	(2) 40 AH	(2) 55 AH	(2) 70 AH	(2) 100 AH	(2) 70 AH
PER CHARGE RANGE (MAX) ^{2,9}	Up to 19.3 km (12 miles)	3W: Up to 11 km (6.9 miles) 4W: Up to 11.5 km (7.2 miles)	Up to 20.9 km (13 miles) ¹⁰	Up to 16.9 km (10.5 miles) ¹⁰	Up to 21 km (13 miles)	Up to 16 km (10 miles)	Up to 28.8 km (17.8 miles)	Up to 17.9 km (11 miles)	Up to 25 km (15.5 miles)	Up to 25 km (15.5 miles) with 40 AH batteries	Up to 30 km (18.6 miles)	Up to 26 km (16 miles)	Up to 20.6 km (12.8 miles)	Up to 40.2 km (24.9 miles) ¹⁶	Up to 25 km (15.5 miles)	Up to 35 km (21.7 miles)	Up to 35 km (21.7 miles)	Up to 35 km (21.7 miles)
BATTERY CHARGER	Lithium Off-Board 2.5A	Off-Board, 2A	Off-Board, 2A	Off-Board, 2A	Off-Board, 3.5A	Off-Board, 3.5A	Off-Board, 3.5A	Off-Board, 3A	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 5A	Off-Board, 5A	Off-Board, 5A	Off-Board, 5A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A
SUSPENSION	N/A	N/A	N/A	Front & Rear	Front & Rear	Front & Rear	Front & Rear	N/A	N/A	Front & Rear	Front & Rear	Front & Rear	3W: Rear 4W: Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear
MAXIMUM WEIGHT CAPACITY	113.3 kg (250 lbs)	118 kg (260 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	170 kg (374.7 lbs)	136 kg (300 lbs)	170 kg (374.7 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	160 kg (352 lbs)	181.4 kg (400 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	158.7 kg (350 lbs)	181.4 kg (400 lbs)	158.7 kg (350 lbs)	181.4 kg (400 lbs)
STANDARD BODY COLOURS	White	Red	Red, Blue ¹	Red, Blue ¹	Grey Street, True Blue	Fire Opal, Pearl White, Sapphire Blue	Candy Apple Red	Red	Viper Blue	Viper Blue	Red	Candy Apple Red	Candy Apple Red	Candy Apple Red, Silver	Candy Apple Red, Mercury Silver	Candy Apple Red, Yellow, Silver	Stone Grey	Black
WEIGHT OF HEAVIEST PIECE ⁴	23.5 kg (56.2 lbs) (does not disassemble)	3W: 13.4 kg (29.5 lbs) 4W: 15.4 kg (34 lbs) (front sections)	15.4 kg (34 lbs) (front section)	16.6 kg (36.6 lbs) (front section)	25.9 kg (57 lbs) (front section)	21.8 kg (48 lbs) (rear section)	34 kg (75 lbs) (rear section)	25.8 kg (57 lbs) (front section)	27.7 kg (61 lbs) (rear section)	29.5 kg (65 lbs) (front section)	50.8 kg (112 lbs) (does not disassemble)	35.2 kg (77.6 lbs) (rear section)	3W: 27.5 kg (60.5 lbs) 4W: 32 kg (70.5 lbs) (front section)	37.6 kg (83 lbs) (front section)	34 kg (74.9 lbs) (rear section)	93 kg (205 lbs) (main frame)	99 kg (218.2 lbs) (main frame)	3W: 92.3 kg (203.4 lbs) (main frame)
3W/4W OPTION	4W	4W & 3W	4W	4W	4W	4W	4W	4W	4W	4W	4W	4W	4W & 3W	4W	4W	4W	4W	3W
TRAVEL MOBILITY						ZERO TURN SERIES				MID-SIZED LUXURY						FULL-SIZED LUXURY		

1 All shroud panels included. 2 Varies with user weight, terrain type, battery amp- hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%. 3 Battery weight not included. 4 Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%. 5 12 AH battery pack weighs 8.8 kg (19.5 lbs.). 6 Durable solid plastic. 7 Deep cycle (AGM or gel cell type recommended) excluding Lithium-ion models. 8 18 AH battery pack weighs 13.4 kg (29.5 lbs.). 9 Tested in accordance with ANSI/RENSA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. 10 Up to 14 miles per charge on 18 AH batteries. 11 Battery weight may vary based on manufacturer. 12 Width of base (not including seat). 13 Does not account for anti-tip clearance. 14 Includes standard seat weight. 15 At midframe 16 Range tested with 31-36 AH Batteries. Standard larger battery size would increase range. 17 6.9 cm x 35.5 cm (2.75"x 14") Rim Only 18 Varies with user weight, terrain type, battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%. NOTE The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

CE
Quality System
Quality Endorsed Company
AU_SCE/E_16-02-21



MODEL NAME	Jazzy® Passport	Go Chair NG®	Jazzy® Select 6	Jazzy® Air 2	Jazzy® 623 2.0	Jazzy® Elite HD	Jazzy® 1450	R-40
WEIGHT CAPACITY	113.3 kg (250 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	136 kg (300 lbs)	204.1 kg (450 lbs) ⁶	273.1 kg (600 lbs)	136 kg (300 lbs)
TURNING RADIUS ¹	61.5 cm (24.25")	64.5 cm (25.4")	55.5 cm (21.87")	61.5 cm (24.25")	50.8 cm (20")	61.9 cm (24.3")	67.3 cm (26.5")	96.5 cm (38") with foot riggings
WIDTH ¹	59.6 cm (23.5")	57.1 cm (22.6")	59.6 cm (23.5")	64.1 cm (25.25")	60.9 cm (24")	61.5 cm (24.2")	74.2 cm (29.25")	63.5 cm (25") at rear wheels
LENGTH ^{1,2}	101.6 cm (40")	83.8 cm (33")	90.1 cm (35.5")	106 cm (42")	90.1 cm (35.5")	90.1 cm (35.5")	97.1 cm (38.25")	88.9 cm (35")
MAXIMUM SPEED ³	Up to 5.7 km/h (3.6 mph)	5.9 km/h (3.7 mph)	Up to 6.4 km/h (4 mph)	Up to 6.4 km/h (4 mph)	Up to 9.6 km/h (6 mph)	Up to 6.4 km/h (4 mph)	Up to 7.2 km/h (4.5 mph)	Up to 9.6 km/h (6 mph)
GROUND CLEARANCE ¹	7.6 cm (3") at motor	4.5 cm (1.8") at frame	4.4 cm (1.75") at motors & at centre frame	7.3 cm (2.9") 2.5 cm (1") at motor bracket	7.6 cm (3") at rear castor	7.6 cm (3")	3.8 cm (1.5")	7.2 cm (2.87")
FRONT WHEELS	20.3 cm (8") solid front castors	15.2 cm (6") solid castors	15.24 cm (6") solid castors	15.2 cm (6") solid castors	15.2 cm (6") solid castors	7.6 cm (3") solid anti-tips	10.6 cm (4") solid anti-tips	22.8 cm (9") pneumatic castors
DRIVE WHEELS	30.4 cm (12") pneumatic	22.8 cm (9") solid	25.4 cm (10") solid	25.4 cm (10") solid	35.5 cm (14") pneumatic	35.5 cm (14") solid	35.5 cm (14") solid	35.5 cm (14") pneumatic
REAR WHEELS	N/A	7.6 cm (3") solid anti-tips	15.2 cm (6") solid castors	15.2 cm (6") solid castor	15.2 cm (6") solid castors	15.2 cm (6") solid castors	22.8 cm (9") castors	7.6 cm (3") solid rear anti-tips
DRIVE TRAIN	2x 180W brushed motors	Two-motor, rear-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, in-line, mid-wheel 6®	Two-motor, front-wheel drive	Two-motor, front-wheel drive	Two-motor, rear-wheel drive
BRAKING SYSTEM	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical	Regenerative and Electro-mechanical
SUSPENSION TYPE	Limited	Limited	Active-Trac® (ATX)	Active-Trac® with Mid-Wheel 6 technology	Active-Trac® (ATX)	Limited	Swing Arm	Adjustable
HIGH-BACK SEAT-TO-FLOOR RANGE	N/A	N/A	53.9 cm - 59 cm (21.25" - 23.25")	53.9 cm - 84 cm (21.25" - 33.1")	52 cm - 59.6 cm (20.5" - 23.5")	50.8 cm - 55.8 cm (20" - 22")	52 cm - 57.1 cm (20.5" - 22.5")	N/A
SPECIALITY SEATING OPTIONS	N/A	N/A	N/A	N/A	Synergy® Seating ^A Tru-Balance ^B	N/A	Synergy® Seating ^A	N/A
SPECIALTY CONTROLS	N/A	N/A	N/A	N/A	Yes	N/A	Yes	N/A
STANDARD ELECTRONICS	50A, PG VSI	40A, PG GC3	40A, PG GC3	40A, VR2	90A, PG VR2	90A, PG VR2	90A, PG VR2	70A, PG VR2
BATTERY SIZE	24 V, 18 AH Lithium-ion (1)	12 V, 18 AH (2)	12 V, 35 AH (2)	12 V, 40 AH (2)	12 V, 55 AH (2)	12 V, 55 AH (2)	12 V, 70 AH (2)	12 V, 50 AH (2)
STANDARD BATTERY CHARGER	2A, off-board, Lithium	2A, off-board	3.5A, off-board	5A, off-board	8A, off-board	5A, off-board	8A, off-board	5A, off-board
PER-CHARGE RANGE ^{9,5}	Up to 15.4 km (9.6 miles)	Up to 14km (8.7 miles)	Up to 24.1 km (15 miles)	Up to 27 km (16.8 miles)	Up to 24.9 km (15.5 miles)	Up to 15.7 km (9.8 miles)	Up to 25.2 km (15.7 miles)	Up to 24.9 km (15.5 miles)
BATTERY WEIGHT ⁷	3.9 kg (8.81 lbs) each	14 kg (31 lbs) battery box	10.5 kg (23.3 lbs) each	14.1 kg (31.2 lbs) each	16.8 kg (37 lbs) each	16.8 kg (37 lbs) each	23.4 kg (51.6 lbs) each	16.8 kg (37 lbs) each
WEIGHT OF HEAVIEST PIECE ⁴	24.4 kg (54 lbs)	16.3 kg (36 lbs)	44.1 kg (97.4 lbs)	91.6 kg (202 lbs) ⁸	62.3 kg (137.5 lbs)	44.9 kg (99 lbs)	88.4 kg (195 lbs)	47.6 kg (105 lbs)
STANDARD SEAT WEIGHT	N/A (seat is integrated with the base) (sling)	13.6 kg (30 lbs)	19.9 kg (44 lbs) (comfort, high-back)	23 kg (50.7 lbs) (high-back)	19.9 kg (44 lbs) (high-back)	23.5 kg (52 lbs) (high-back)	25.8 kg (57 lbs) (high-back)	N/A (seat is integrated with the base) (sling with power tilt)
STANDARD SEAT SIZE	41.9 cm x 44.4 cm (16.5"x 17.5")	43.1 cm x 45.7 cm (17"x 18")	45.7 cm x 45.7 cm (18"x 18")	40.6 cm x 45.7 cm (16"x 18") 45.7 cm x 45.7 cm (18"x 18") 50.8 cm x 45.7 cm (20"x 18")	45.7 cm x 45.7 cm (18"x 18") 50.8 cm x 45.7 cm (20"x 18")	45.7 cm x 45.7 cm (18"x 18") 50.8 cm x 50.8 cm (20"x 20") 55.8 cm x 50.8 cm (22"x 20")	60.9 cm to 81.2 cm (24" to 32")	40.6 cm x 45.7 cm (16"x 18")
COLOUR OPTIONS	Pewter	Ruby Red, Pearl White	Ruby Red	Black Oynx, Pearl White, Pink Topaz, Garnet Red	Candy Apple Red	Jazzy Red, Jazzy Blue	Candy Apple Red, Viper Blue	Silver
FOLDABLE		NEW GENERATION		JAZZY POWER CHAIRS				FUSION

¹ Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or – 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections. ² Without front riggings. ³ Varies with user weight, terrain, battery condition and tire pressure. ⁴ Does not include seat or battery weights. ⁵ Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, - 5%. ⁶ Maximum weight capacity is reduced to 400 lbs. (181 kg) on 46 cm (18") deep seat configurations. ⁷ Battery weight may vary based on manufacturer. ⁸ Seat weight included (because tools are required to remove the seat). Battery weight not included. ⁹ Varies with user weight, terrain, battery condition and tire pressure. ^AInternational configuration shown **SEATING: A** For Synergy® Seating. Contact your nearest Pride® stocklist for more information ^B Quantum® dealers only **NOTE** The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.

AU JZEZE_16-02-21