

120 TW Dump Truck Triple View




KEY FEATURES


- ENHANCED SAFETY AND STABILITY
- 180°SWIVEL ABRASION RESISTANT BODY
- 4WD HYDROSTATIC TRANSMISSION
- 3 MODE / 4 WHEELS STEERING
- MAXIMUM MANEUVERABILITY
- LEVEL II FOPS PROTECTION SYSTEM
- ENCLOSED AIR-CONDITIONED CABIN
- ROBUST AND RELIABLE


120TW DUMP TRUCK




PERFORMANCE			
MODEL		120TW	
Maximum Load Capacity		12000 Kg	
SAE Heaped Capacity		6000 L	
Struck Capacity		4900 L	
Unladen Weight		7960 Kg	
Body External Turning Radius	(1)	5150 mm	
Internal Wheels Turning Radius	(2)	2475 mm	
External Wheels Turning Radius	(3)	4650 mm	
MAX Driving Speed		35 Km/h	
MAX Gradeability with Full load		40 %	









STANDARD SPECIFICATIONS:

STANDARD SPECI	FICATIONS:	
ENGINE		
Model	Perkins 1104 TA Tier IIIA	
Engine Power	(83 Kw/113 Hp)	
TRANSMISSION		
Type/Model	Automotive Hydrostatic Transmission	
Front Axle	+ - 8° Oscillating Steering Axle	
Rear Axle	Fixed Steering Axle with Flanged Gearbox	
Diiferential Locks	Front Automatic, Rear Hydraulically controlled	
Maximum Travel Speed	35 Km/h	
Gears	4 Forward and 4 Reverse, 2 Electro-Hydraulic HI - LO + 2 Speed Transmission	
Inching Control	Standard	
BRAKES		
Service Brakes	Multi-discs Hydraulic Service Brakes on Both Axles with Fail-Safe circuit	
Parking Brake	Multi-discs Hydraulic Parking Brake with Automatic Activation	
TYRES		
Standard Tyres	Trelleborg High Floatation 50	00/60 R22.5
CABIN		
High-Visibility 3 Position swivel driving platform		Std
Enclosed Cabin, ROPS / FOPS II Approved Structure		Std
Automotive Air-Conditioning System		Std
HYDRAULIC SYSTEM		
Hydraulic Gear Service Pump for utilities		63 l/min
Hydraulic Gear Service Pump for Steering and Brakes		48 l/min
BODY		
Certified HARDOX 500 Abrasion Resistant Body Structure		Std
180° swivel body		Std
MISCELLANEOUS		
Fuel tank capacity		95 L
Hydraulic System capacity		140 L
Electrical system voltage		12v
AVAILABLE OPTIONS		
Deutz TCD 3.6L Tier IIIB Engine - DOC (90 Kw/121 Hp)		Optional
Perkins StageV Engine -DPF & SCR (90 Kw/121 Hp)		Optional
Low profile Agricultural tyres		Optional
Pneumatic Suspension Grammer Seat		Optional
360° Vision Cameras System		Optional
LED Work lights Kit		Optional
Rugged bars protection kit		Optional
Hydraulic auxiliary line with joystick control		Optional





NIMAC PACIFIC

Nimac Pacific reserves the right to modify and update the contents of this at any time. Information and technical data are as available at time of printing.

For further information visit ${\bf www.nimacpacific.com.au}$