

## HCS-3900M/20 Series Compact Digital Conference System Main Units

- 256×64 OLED displays the status and the menu of system configuration
- Adopt fully digital audio transmission technology between the main unit and the conference unit
- Can be directly employed in small and medium-sized meeting rooms without amplification system due to the built-in monitor loudspeaker
- With web page control function, the user can access the IP address of main unit from web browser to handle meeting management
- Multiple speech modes including OPEN/OVERRIDE/VOICE/APPLY/PTT to meeting various conference needs
- Automatic video tracking, when cooperating with camera and video switcher unit
- One USB interface and one SD card slot for conference audio recording and playback
- Detect the unit's LED before the meeting with built-in unit detection facilities
- Supporting "PnP" (plug and play)
- Perfect connection to central control system



### Function list

Model	HCS-3900MA/20	HCS-3900MB/20
Speech	•	•
Recording	•	•
256×64 OLED	•	•
6P sockets	•	•

### Technical Specifications

Electrical	
Microphone connectivity	50
Frequency response	40~16000Hz
SNR	≥90dBA
Mechanical	
Dimensions (h×w×d)	45×483×213 mm
Weight	3.2 kg



**TAIDEN INDUSTRIAL CO., LTD.**

6/F, Block B, Future Plaza, 4060 Qiaoxiang Rd, Nanshan District Shenzhen, 518053 P.R.China

TEL: (+86)755-86621810 86621811 86621812

Website: [www.taiden.com](http://www.taiden.com)

Copyright ©202309 TAIDEN Industrial Co., Ltd. All Rights Reserved.

# TAIDEN®

## Compact Digital Conference System



# Compact Digital Conference System

HCS-3900 Series Compact Digital Conference System, designed for small and medium-sized meeting rooms, adopts advanced fully digital audio technology to ensure the participants' voices are clear and natural. The system features microphone management, automatic video tracking, video switching, conference audio recording, etc.



## Flexible Use

HCS-3900 Series of conference units have built-in speaker and headphone jack for delegates to choose the listening way they prefer. The conference units can be installed on the desk and are convenient for use.

## Easy Wiring

One single cable can simultaneously transmit high-quality audio and control signals, meeting the wiring requirements of various venue environments.

## Simple Operation

The HCS-3900 conference system allows users to access the main unit from the web browser for detailed parameter settings, realizing more powerful management and control.

## Stable System

With high-quality hardware and stable software structure, HCS-3900 series provides a stable, continuous conferencing experience whether for long-time conferences or frequent use.

## HCS-3900 Series Conference Units

- Equipped with 5PIN microphone socket, stem microphone ordered separately
- Stem microphone can be unplugged during adjournment, easy to maintain
- Physical buttons and Braille simplify operation for all users (only HCS-3940 Series)
- Gain of each microphone is adjustable separately, fitting the each speaker's voice to achieve perfect effect
- Integrated high-pass filter (low-cut switch) can cut low frequency elements from the audio when needed
- Built-in Hi-Fi loudspeaker mutes automatically when microphone is active, avoiding feedback
- Automatic video tracking when cooperating with camera and video switcher unit



HCS-3940 Series



HCS-3938 Series