

NUUO CT-8000 Series

End to End • Unified • Software Centric



- ▶ Rock Solid Rack Mount Server
- ▶ Annual Upgrade Included
- ▶ Stable Recording Performance

NUUO IP Appliance



Design Highlights

- Embedded Mainconsole IP+
- Video analysis included - NUUO Smart Guard
- Support advanced video analysis - NUUO IVS
- Professional rack mount server
- 3rd party data party available - Point of sale, access control and LPR

Premiere Feature


- Recording throughput up to 250Mbps
- 128ch remote live video connections
- Storage group for better video and storage management
- Various recording technologies - Boost Recording, Dual Recording, IVS event recording, individual retention condition
- Support auto load balancing and storage group
- Support camera edge storage to automatically or daily retrieve video data from camera to IP Appliance¹
- Support camera multi-stream function in both live view and playback
- Watermarking Authentication
- Internal diagnostic service (Available Q3 2015)
- POS, I/O device, LPR and access control integration
- Windows active directory
- Privacy mask
- iPhone, iPad, Android (Liveview, 1CH playback and push notification)
- Dual password validation
- Edge motion detection from IP camera¹
- OnGuard (software watchdog)
- Auto backup
- Flexible video recycle management options
- Digital PTZ and camera multi-view
- Friendly GUI recording schedule
- Two-way audio

Specification

Model Name	CT-8000IP-P-25	CT-8000IP-P-32	CT-8000IP-P-36
Type		Rack-mount 2U	
Embedded License	25ch	32ch	36ch
CPU	Intel Core i5-2400 3.1G		
RAM	DDR3-1333 4GB x 2		
Server Operation System	Win7 Ultimate 64bit		
Number of Drives	7xSATA II		
Max Storage Per Drive	4TB		
Max Internal Total Storage	28TB		
Recording Throughput	Up to 250Mbps		
I/O Interface	2 x USB3.0; 2 x USB2.0; 1 x eSATA (for DAS)		
LAN	2 x Gigabit Port, RJ45		
LAN Transmission Speed	10/100/1000 Mbps		
Voltage	100~240V		
Power Consumption	Full loading: 160W Max: 500W		
Dimensions (H x W x D)	88 x 447 x 583 mm		
Weight (without HDD)	13.2 kg (29.1 lbs)		
Temperature (Operating with HDD)	Operating: 0°C~40°C		
Humidity (Operating)	Operating: 5%~95%		
3 rd Party Support	Support third party Point of Sale, Access Control and License Plate Recognition		
External I/O Box	External I/O box SCB-A08 (RJ-485 to RJ-45)		

¹. Check http://www.nuuo.com/SupportCamera.php?node_id=4#3 for NUUO Mainconsole camera support list

NUUO Network Storage




Design Highlights

- High Recording Throughput up to 500Mbps
- Fully compatible with NUUO Crystal™
- Easy WEB Configuration

Specification

Model Name	CT-8000ES	CT-8000ES-RP
Type	Rack-mount 2U	
CPU	Intel Core i5	
Server Operation System	Linux	
Number of Drives	8xSATA II	
Max Storage Per Drive	4TB	
Max Internal Total Storage	32TB	
RAID Level	RAID 0,1,5,10	
I/O Interface	2 x USB3.0; 2 x USB2.0; 1 x eSATA (for DAS)	
LAN	2 x Gigabit Port, RJ45	
LAN Transmission Speed	10/100/1000 Mbps	
Voltage	100~240V	
Power Consumption	Full loading: 150W Max: 500W	Full loading: 160W Max: 500W (Redundant Power)
Dimensions (H x W x D)	88 x 447 x 583 mm	
Weight (without HDD)	11.4 kg (25.1 lbs)	13.2 kg (29.1 lbs)
Temperature (Operating with HDD)	Operating: 0°C~40°C	
Humidity (Operating)	Operating: 5%~95%	
General		
Network File Protocol	NFS	
Compatible NVR	NUUO Crystal™ (above v3.0.0)	
Hardware Watchdog	Yes	
HDD Compatibility	Refer to http://www.nuuo.com/SupportCamera.php?node_id=12	
Supported Languages (17 languages)	Czech, Chinese(Simplified), Chinese(Traditional), English, Finnish, French, Germany, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Spanish, Swedish, Thai, Turkish	

NUUO Crystal™ & Titan NVR



Feature Highlights

Client Highlights

- System Navigator service for Multi-Site management
- Client Camera View Layout Wizard¹
- Embedded Context Sensitive Manual¹
- 3rd party data overlay on videos, event search and keyword search¹
- NUUO Image Fusion Technology –stitch up to 10 cameras together
- NUUO Advanced adjustable fisheye dewarp tool for all fisheye cameras¹
- Instant Playback on live view, e-map and event list
- Twin Clients to support identical, full featured software client and web client
- Up to 3 channels simultaneous motion search¹

Server Highlights

- Recording server failover¹
- Volume group to distribute camera to assigned volumes for load balancing¹
- Individual Retention Condition (IRC) per device¹
- Schedule-based and input-triggered boosting record¹
- Support hardware watchdog and software watchdog³
- Camera template management tool¹
- Support stream profile for remote live view bandwidth control (Original/ 500kbps / 100kbps)
- Camera multiple stream setting support¹
- Internal diagnostic service¹
- Watermarking Authentication

Specification

Type	Tower		Rack-mount 1U		Rack-mount 2U		Rack-mount 2U (Redundant Power)	
Model Name	CT-4000	NT-4040	CT-4000R	NT-4040R	CT-8000R	NT-8040R	CT-8000RP	NT-8040RP
Recording Throughput	250 Mbps (MAX), 150 Mbps (OPTIMAL)				CT-8000 Series : 250 Mbps(1 Volume Group) 400 Mbps (2 Volume Group) 550 Mbps (3 Volume Group) NT-8000 Series : 250 Mbps			
Number of Live View Spot-out(Local display)	CT-4000 Series : 4CH per View, View tour to 64CH NT-4000 Series : 1CH per View, View tour to 64CH				16CH per View, View tour to 64CH			
CPU Model	Intel Atom				Intel Core i5			
Number of Drives	4xSATA II				8xSATA II			
Max Storage Per Drive ⁵	6TB				6TB			
Max Internal Total Storage ⁴	24TB				48TB			
RAID Level	RAID 0, 1, 5, 10				RAID 0, 1, 5, 10			
I/O Interface	6 x USB 2.0 (for mouse, UPS); 1 x eSATA (for DAS)		4 x USB 2.0 (for mouse, UPS); 1 x eSATA (for DAS)		2 x USB3.0; 2 x USB2.0; 1 x eSATA (for DAS)			
LAN	2 x Gigabit Port, RJ45				2 x Gigabit Port, RJ45			
LAN Transmission Speed	10/100/1000 Mbps				10/100/1000 Mbps			
Voltage	100~240V				100~240V			
Power Consumption	Full loading:50W Max: 250W				Full loading: 150W Max: 500W		Full loading: 160W Max: 500W (Redundant Power)	
Dimension (HxWxD)	212 x 200 x 318 mm		45 x 447 x 429 mm		88 x 447 x 583 mm		88 x 447 x 583 mm	
Weight (Without Drive)	5.3 kg (11.7 lbs)		6.0 kg (13.2 lbs)		11.4 kg (25.1 lbs)		13.2 kg (29.1 lbs)	
Temperature	Operating: 0°C~40°C				Operating: 0°C~40°C			
Humidity	Operating: 5%~95%				Operating: 5%~95%			
Supported Languages (17 languages)	Czech, Chinese(Simplified), Chinese(Traditional), English, Finnish, French, Germany, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Spanish, Swedish, Thai, Turkish							

License Type

License	Part Name	License	Part Name
Ultimate	CT-CAM-ULT CV-CAM-ULT ⁷	Point of Sale	CT-POS-Generic
Enterprise	CT-CAM-ENT CV-CAM-ENT ⁷	Access Control	CT-ACC-Generic
Professional ⁶	CT-CAM-PRO	Upgrade (Enterprise → Ultimate)	CT-CAM-UPU CV-CAM-UPU ⁷
Titan Expansion	NT-TITAN-UP	Upgrade ⁶ (Professional → Enterprise)	CT-CAM-UPE

- ¹ Available with Crystal™ Only
- ² Available with Crystal™ NuClient version 3.0 and above
- ³ Available with CT-8000R(P) and NT-8040R(P)
- ⁴ Version below v3.0 (not including v3.0), the maximum size of volume cannot exceed 16TB
- ⁵ Refer NUUO web site for hard drive compatibility list (http://www.nuuo.com/SupportCamera.php?node_id=12#)
- ⁶ Not available in North America
- ⁷ Pure NUUO Crystal™ Software on VMware vSphere

Compatible Access Control Manufacturers



NUUO Inc. | B1, No.207-1, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan Tel: +886.2.7739.2260 Fax: +886.2.7703.3377
 NUUO US Inc. | 690 N. Berry Street, Suite B, Brea, California 92821, USA Tel: +1.714.990.1688 Fax: +1.714.990.1689 Toll Free: +1.877.241.7035
 NUUO African Representative | Fancourt Office Park, Building 7, 1st Floor Right, Cnr Felstead & Northumberland, Northriding, 2169, South Africa Tel: +27.11.704.6845

Made in Taiwan V.2015 / 10 (Global)