RUSTICO 6X6 AND 6X9

Small square and oversized brick shapes with a slightly dimpled surface. Chamfered edges and square corners make these pavers an elegant choice.



paver-**shield™** pavers

paver-shield[™] has a tight, smooth surface texture and will not expose heavy aggregate as it wears. Ultra-dense surface has more color and more protection. Nicolock has color from top to bottom throughout the paver ensuring a lifetime of beauty. Iron oxide pigments are guaranteed not to fade!




Rustico 6x9 | Color: Fire Island Blend



RUSTICO 6X6 AND 6X9

	WIDTH	LENGTH	THICKNESS	PCS / SF	SF / PALLET	PCS / PALLET	LBS / PALLET
Α	6"	6"	23/8"	4	120	480	3,027
В	6"	9"	2¾"	3	113	300	2,982









Blend









Blend



Blend*

























Cappuccino Blend*

Caramel Tan* (6x9 only)

Chesapeake Blend*

Crab Orchard Blend*

Fire Island Blend

Golden Brown Blend

Graphite Pearl Blend (6x9 only)

Lilac Blend (6x9 only)

Marble Blend'

Mocha Blend (6x9 only)

Oceanic Blue* (6x9 only)

Pennsylvania (6x9 only)

South Bay

Blend*


INSTALLATION GUIDELINES: SAND

After excavation, compact the sub grade and install a woven separation fabric if needed. Spread and compact a base of clean, dense graded aggregate (road base). Typical compacted base thickness is 4-6" for pedestrian applications. Pavers are set on a loosely screened 1" bed of graded, clean concrete sand. Maintain a joint size of 1/16" - 3/16". When pavers are set, compact paving stones into sand with mechanical plate vibrator. Joint sand may be spread over paving stones during compaction. Installed pavers should be set 1/8" to 1/4" above final elevations to compensate for any potential settlement. Spread clean dry sand over surface and broom sweep to fill joints. Run vibrator one final time after filling joints.

CROSS-SECTION OF TYPICAL INSTALLATION

Pavers Edge Resistant Pavers should slope slightly away from building for water drainage **Pedestrian Traffic** 4" - 6" compacted aggregate 1" Bedding Sand

NICOLOCK PAVING STONE 1"-31/8" THICK



NOTE: All measurements are nominal. Variance in square footage or linear footage coverage can be up to 5% depending on joint width. The possible occurrence of efflorescence does not affect the structural integrity of the product. Efflorescence is a normal occurrence in concrete products and will dissipate with normal weathering. The use of concrete as a base or setting bed may increase the possibility of efflorescence.

CAUTION: Always use a plate compactor with a pad when installing any textured paving stone.















