

Silex Touch-Clarity ID98

98" Interactive Display



Main Features

- Anti-Glare tempered chock-proof glass
- Enhanced visual effect and improved touch experience
- High-speed 20-point touch for smooth and fast writing experience
- Optional standard OPS slot, integrated plug-in design with easy upgrade and maintenance
- Easily accessible front ports: 3 USB type A, 1 USB type C, 1 HDMI input, 1 Touch USB
- 15Wx2 front speakers
- Front button one key start for simple and convenient operation
- Android 11.0/13.0 OS, with practical whiteboard and annotation software features

Specifications

Display:

- Screen size: 98inch
- Screen assembly process: Zero-fit
- Backlight: DLED
- Pitch: 0.1625x0.4875mm
- Display area: 2158.85*1214.35mm
- Ratio: 16:9
- Resolution: 3840 x 2160 UHD / 4K
- Brightness: 350cd/m²
- Contrast: 1200:1(Typ.)
- Color: 1.07 Billion
- Viewing angle: 178°,178°
- Response time: ≤8ms
- Speaker power: 15Wx2
- Color gamut (Typ.): 72%NTSC
- Support HDR

Touch:

- Touch type: IR
- Touch points: Android 20 points/
Windows 20 points
- Touch drive mode: HID drive-free
- Sensing method: Finger, writing pen or
other non-transparent touch sensitive
media
- Resolution: 32768x32768
- Touch port: USB 2.0
- Response time: ≤10ms
- Touch accuracy: 1mm
- Touch diameter: Single point ≥2mm.
Multipoint ≥3mm

Tempered glass:

- Thickness: 4mm
- Hardness: Mohs 7H
- Surface treatment: AG Anti-Glare

Camera (optional):

- Built-in camera in the top center
- Sensor: CMOS 1/2.0"
- Field of view (FOV): 120°
- Format: MJPG/YUY
- Pixel: 13MP/48MP
- Support face tracking (optional)

Microphone (optional):

- Built-in microphone in the top center
- Number of microphone arrays: 8-way,
omnidirectional, noise-canceling
microphone
- Pickup distance: 0~10m
- Support 3D noise reduction

Android:

- Android system version: 11.0/13.0
- Main chip: Amlogic T982
- CPU Architecture: Quad-core 64Bit CPU
- CPU Working frequency: 1.4GHZ, 4*A55
- GPU: Mali G52 MC8
- 4G/8G DDR, 32G/64G/128G Storage

Network:

- LAN: Adaptive10M/100M/1Gbps
- Location: onboard, built-in
- Configuration: WiFi4 + WiFi5
- Protocol: Wireless 802.11 b/g/n. Hotspot
802.11 a/b/g/n/ac
- Working frequency: Wireless
2.4~2.5GHz Hotspot 2.4~2.5GHz and
5.15~5.825GHz
- Working distance: 0~12m

Bluetooth:

- Version: 5.0
- Working frequency: 2.4GHz
- Working distance: 0~12m

IO/port:

- Front: USB3.0 type A, HDMI(2.0), Touch USB2.0 type B, USB type C
- Rear: Mic in 3.5mm, RJ45, RS232 (DB9), Line out, Touch USB2.0 type B, HDMI in, USB2.0
- Optional OPS module

Power:



- Working voltage: AC100~240V/50~60Hz
- Maximum power: $\leq 500W$
- OPS power supply: DC 12-19V/1.0-7.0A supports OPS & OPS-C specifications
- Standby power consumption: $< 0.5W$

Other Specifications:

- Product size: 2216*1334.66*105.19mm
- Size including bracket: 2216*1334.66*135.19mm
- Distance between holes: 1000*400mm
- Wall mounting dimensions: 2236*1354.66*135.19mm
Installation principles: widening 20mm on two sides
- Package size: 2386*250*1468.6mm
Package: carton box
- Net Weight/ Gross Weight: 98Kg/125Kg
Net weight (product weight) Gross weight (including accessories and package)
- Installation: Wall mounting (standard)
- Storage environment: Storage temperature: $-20^{\circ}C \sim 55^{\circ}C$; Storage humidity: 5%RH~90%RH
- Working environment: Working temperature: $0^{\circ}C \sim 40^{\circ}C$; Working humidity: 10%RH~80%RH
- Altitude: $\leq 5000m$ above sea level

Accessories:

- Wall mount bracket, expansion screw, touch pen, 1.5m power cable, warranty card, remote control, manual





© 2024 SilexPro. All rights reserved. SilexPro and any SilexPro product or service name or logo used herein are trademarks of SilexPro. All other trademarks used herein belong to their respective owners. The trademarks and logos displayed herein may not be used without the prior written consent of SilexPro or their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of SilexPro.

www.Silexpro.com