

Silex LED-Clarity P0.9 IMD 4in1 Indoor



Main Features

- Small pixel density/High resolution
- High refresh rate
- Wide viewing angles
- Premium LED: Bigger chip size, high brightness, slow decay of brightness, longer lamp life, high refresh rate
- IMD 4in1 technology: Energy Efficiency, Superior Durability – water resistant (IP54), moisture resistant, dustproof, shockproof, UV resistant
- Easy installation
- Front service, easy maintenance

Specifications

Module Specifications:


- Pixel Pitch: 0.9375mm
- Led Type: IMD 4in1
- Module Size: 150x168.75mm
- Module Resolution: 160x180 pixels

Cabinet Specification:

- Cabinet Size: 600x337.50mm
- Cabinet Resolution: 640x360 pixels
- Module Qty: 4x2pcs
- Cabinet Materials: Die-casting Aluminium
- Cabinet Weight: 4Kg

Screen Parameters:

- Brightness: 600cd/m²
- Brightness uniformity: ≥98%
- Scanning Mode: 1/48scan
- Viewing Angle: H:160°;V:160°
- Viewing Distance: >1m
- Gray Level: 16 Bit
- Contrast ratio: ≥5000:1
- Refresh Frequency: ≥3840 Hz
- Power Input: AC 220V
- Power Consumption: Max: 400W/m², Average: 130W/m²
- MTBF—hours: >10,000 hours
- Life—hours: ≥100,000 hours
- IP Grade: IP54
- Operating Temperature: -20° C~ 50° C
- Storage Humidity: 10° C~60° CRH
- Control System: Novastar
- Power Supply: Standard
- Maintenance Access: Front service





© 2024 SillexPro. All rights reserved. SillexPro and any SillexPro product or service name or logo used herein are trademarks of SillexPro. All other trademarks used herein belong to their respective owners. The trademarks and logos displayed herein may not be used without the prior written consent of SillexPro or their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of SillexPro.

www.Sillexpro.com