

Silex Touch-Clarity PCAP86

86" Interactive Display





Main Features

- Advanced touch technology: Incell Touch is an advanced technology that combines
 the display and touch functions by embedding touch sensors inside the panel,
 delivering higher touch performance and picture quality
- 4K/UHD 3840x2160 resolution
- Full lamination technology for improved contrast, neatness, clarity and screen protection
- 20 touch points PCAP touch technology for fluent, fast and accurate writing.
- Wireless screen-sharing with multiple screens interaction and smooth switching between screens through the touchscreen
- Single versatile power button for power On-Off, Standby mode and Eco mode
- Video conferencing support via an optional built-in or plug-in 48MP UHD camera, 2x20W built-in speakers, 6 or 10 array microphones (optional).











Specifications

Display:

Screen size: 86inchBacklight type: DLEDDisplay type: LCD

Pitch: 0.4935x0.4935mmDisplay area: 1895*1065mm

• Ratio: 16:9

Resolution: 3840 x 2160 UHD / 4K

Brightness: 350cd/m²
Contrast: 1200:1(Typ.)

Color: 10 bit

Viewing angle: 178°,178°

Refresh rate: 60HzResponse time: 8ms

Operation (Hours/Day): 24/7

Color Gamut: 88%

Lifespan (Typ): 60000Hrs

Optional OPS

Touch:

Touch type: P-cap IncellTouch points: 20 points

Touch drive mode: HID drive-free
 Sensing method: Finger or capacitive

Resolution: 32767x32767

Touch system communication port: USB
 20

Touch accuracy: ≤2mmTouch Diameter: 7mmResponse Time: 35ms



Mainboard configuration (982 version):

System: Android 11.0 or 13.0 (optional Windows System)

 Configuration: 4G DDR, 32G Storage (optional 8G+128G)

CPU: Quad Core Cortex-A55

• GPU: MALI G52 MP2

• WIFI: 2.4G, 2.4G+5G dual WIFI. Built-in Bluetooth 5.0

Mainboard configuration (311D2 version):

System: Android 13 (optional Windows System)

 Configuration: 4G DDR, 32G Storage (optional 8G+128G)

 CPU: Quad Core Cortex-A73 and Quad Core Cortex-A53 2.2G

GPU: Dual-core MALI G52

• WIFI: Built-in 5G(compatible for 2.4G). WIFI 6. Built-in Bluetooth

Camera (Optional):

Resolution: 48MPConnectivity: USB2.0

• FOV: 120°

Microphone (Optional):

Michrophone Type: Linear ring array microphone

• Number: 4

Pickup Distance: 0-10mPickup Angle: 0-180°

Speaker:

Sound Track: 2.1

Speaker(982 version) 8Ω 2x15W

• Speaker(311D2 version) 8Ω 2x20W



Power:

Working voltage: 90~264V/50 or 60Hz

• Consumption: 500W

Standby power consumption: ≤0.5W

Other Specifications:

Product size: 1958*1129*88mm
Package size: 2080*1340*220mm
Not Weight Gross Weight 62Kg/90Kg

Net Weight/ Gross Weight: 62Kg/80Kg
 Net weight (product weight) Gross weight (including accessories and package)

VESA: 800x600mmScrew: M8x25mm



IO Interfaces (982 version)

 1xCOAX, 1xRS232, 1xMINI AV, 1xMINI AV OUT, 1xEarphone, 1xMIC IN,1xRJ45 IN, 1x RJ45 OUT, 1x HDMI 1, 1xHDMI 2, 1xTOUCH OUT, 1xANDROID USB2.0, 3xUSB3.0, 1xTF CRAD, 4WIFI


 Optional: 1xVGA, 1xPC AUDIO, 1xMINI YPBPR, 1xDP IN, 1xHDMI OUT


IO Interface (311D2 version)

 1xCOAX OUT, 1xMIC IN, 1xLINE OUT, 1xMICRO-USB, 1xRS232, 1xTOUCH, 1xHDMI IN, 1xHDMI OUT, 1xRJ45, 2xUSB 2.0, 1xTF SLOT, 3xWIFI

Accessories:

Power cord, WIFI antennas, pen, remote control







© 2024 SilexPro. All rights reserved. SilexPro and any SilexPro product or service name or logo used herein are trademarks of SilexPro. All other trademarks used herein belong to their respective owners. The trademarks and logos displayed herein may not be used without the prior written consent of SilexPro or their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of SilexPro.