

# Silex LED-Clarity P1.2 COB Indoor



## Main Features

- Small pixel density/High resolution
- High refresh rate
- Wide viewing angles
- Premium LED: Bigger chip size, high brightness, slow decay of brightness, longer lamp life, high refresh rate
- COB technology: Superior durability, water resistant, moisture resistant, dustproof, shockproof, UV resistant
- Easy installation
- Front service, easy maintenance

# Specifications

## Module Specifications:

- Pixel Pitch: 1.25mm
- Led Type: COB
- Module Size: 300x168.75mm
- Module Resolution: 240x135 pixels

## Cabinet Specification:

- Cabinet Size: 600x337.5x39mm
- Cabinet Resolution: 480x270pixels
- Module Qty: 2x2pcs
- Cabinet Materials: Die-casting Aluminium
- Cabinet Weight: 4Kg

## Screen Parameters:

- Brightness: 600cd/m<sup>2</sup>
- Brightness uniformity: ≥98%
- Scanning Mode: 1/45scan
- Viewing Angle: H:160°;V:160°
- Viewing Distance: >1.3m
- Gray Level: 16 Bit
- Contrast ratio: 15000:1
- Refresh Frequency: ≥3840 Hz
- Power Input: AC 110-240V
- Power Consumption: Max: 300W/m<sup>2</sup>, Average: 100W/m<sup>2</sup>
- MTBF—hours: >10,000 hours
- Life—hours: ≥100,000 hours
- IP Grade: IP40/IP20
- Operating Temperature: -20° C~ 50° C
- Storage Humidity: 10° C~70° CRH
- Control System: Novastar
- Power Supply: standard
- Maintenance Access: Front service





© 2025 SilexPro. All rights reserved. SilexPro and any SilexPro product or service name or logo used herein are trademarks of SilexPro. All other trademarks used herein belong to their respective owners. The trademarks and logos displayed herein may not be used without the prior written consent of SilexPro or their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of SilexPro.

[www.Silexpro.com](http://www.Silexpro.com)