

Product Information							Physical Information		Photometric Characteristic				
Watts	Bulb	Base	Item#	Description	Voltage (V)	Case Qty.	Dia (in)	MOL (in)	Beam Angle	Spread	Initial Lumens (lm)	Avg. Life (Hrs)	UPC
PAR16 Series - Medium Screw Base													
60	PAR16	E26	3000	* 60PAR16/NSP/120	120	40	2.88	2.00	10°	Narrow Spot	650	2000	844366030000
60	PAR16	E26	3001	* 60PAR16/NFL/120	120	30	2.88	2.00	30°	Narrow Flood	650	2000	844366030017
60	PAR16	E26	3062	* 60PAR16/NSP/130	130	12	2.88	2.00	10°	Narrow Spot	650	2000	844366030628
				@ 120 volts approximate 53 watts, 495 lumens, 4000 hours									
60	PAR16	E26	3063	* 60PAR16/NFL/130	130	12	2.88	2.00	30°	Narrow Flood	650	2000	844366030635
				@ 120 volts approximate 53 watts, 495 lumens, 4000 hours									
75	PAR16	E26	3002	* 75PAR16/NSP/120	120	40	2.88	2.00	10°	Narrow Spot	900	2000	844366030024
75	PAR16	E26	3003	* 75PAR16/NFL/120	120	30	2.88	2.00	30°	Narrow Flood	900	2000	844366030031
75	PAR16	E26	3064	* 75PAR16/NSP/130	130	12	2.88	2.00	10°	Narrow Spot	900	2000	844366030642
				@ 120 volts approximate 66 watts, 685 lumens, 4000 hours									
75	PAR16	E26	3065	* 75PAR16/NFL/130	130	12	2.88	2.00	30°	Narrow Flood	900	2000	844366030659
				@ 120 volts approximate 66 watts, 685 lumens, 4000 hours									

***Items only available for special orders**