

Product Information							Physical Information		Photometric Characteristics				
Watts	Bulb	Base	Item#	Description	Voltage (V)	Case Qty.	Dia (in)	MOL (in)	Beam Angle	Spread	Initial Lumens (lm)	Avg. Life (Hrs)	UPC
PAR38 Series - Medium Screw Base													
90	PAR38	E26	3078	* 90PAR38/NSP/120	120	15	5.32	4.76	9°	Narrow Spot	1270	2500	844366030789
90	PAR38	E26	3048	* 90PAR38/SP/120	120	15	5.32	4.76	12°	Spot	1270	2500	844366030482
90	PAR38	E26	3049	* 90PAR38/FL/120	120	15	5.32	4.76	30°	Flood	1270	2500	844366030499
90	PAR38	E26	3050	* 90PAR38/WFL/120	120	15	5.32	4.76	50°	Wide Flood	1270	2500	844366030505
90	PAR38	E26	3079	* 90PAR38/NSP/130	130	15	5.32	4.76	9°	Narrow Spot	1270	2500	844366030796
				@ 120 volts approximate 79 watts, 1000 lumens, 5000 hours									
90	PAR38	E26	3051	* 90PAR38/SP/130	130	15	5.32	4.76	12°	Spot	1270	2500	844366030512
				@ 120 volts approximate 79 watts, 1000 lumens, 5000 hours									
90	PAR38	E26	3052	* 90PAR38/FL/130	130	15	5.32	4.76	30°	Flood	1270	2500	844366030529
				@ 120 volts approximate 79 watts, 1000 lumens, 5000 hours									
90	PAR38	E26	3053	* 90PAR38/WFL/130	130	15	5.32	4.76	50°	Wide Flood	1270	2500	844366030536
				@ 120 volts approximate 79 watts, 1000 lumens, 5000 hours									

***Items only available for special orders**