

Product Information							Physical Information		Photometric Characteristics						
Watts	Bulb	Base	Item#	Description	Voltage (V)	Case Qty.	Dia (in)	MOL (in)	CBCP (cd)	Beam Angle	Spread	Initial Lumens (lm)	Avg. Life (Hrs)	Color Temp (K)	UPC
PAR38 Series - Medium Screw Base															
100	PAR38	E26	3054	*100PAR38/SP/120	120	15	5.32	4.76	-	12°	Spot	1500	2500	-	844366030543
100	PAR38	E26	3055	*100PAR38/FL/120	120	15	5.32	4.76	-	30°	Flood	1500	2500	-	844366030550
100	PAR38	E26	3056	*100PAR38/WFL/120	120	15	5.32	4.76	-	50°	Wide Flood	1500	2500	-	844366030567
100	PAR38	E26	3057	*100PAR38/SP/130	130	15	5.32	4.76	-	12°	Spot	1500	2500	-	844366030574
				@ 120 volts approximate 88 watts, 1200 lumens, 5000 hours											
100	PAR38	E26	3058	*100PAR38/FL/130	130	15	5.32	4.76	-	30°	Flood	1500	2500	-	844366030581
				@ 120 volts approximate 88 watts, 1200 lumens, 5000 hours											
100	PAR38	E26	3059	*100PAR38/WFL/130	130	15	5.32	4.76	-	50°	Wide Flood	1500	2500	-	844366030598
				@ 120 volts approximate 88 watts, 1200 lumens, 5000 hours											

***Items only available for special orders**