

| Product Information | | | | | | | Photometric Characteristics | | | | | |
|---|------|-------------|-------|------------------|-----------|----------|-----------------------------|------------------|-----------------|----------------|-----|--------------|
| Watts | Bulb | Base | Item# | Description | Case Qty. | MOL (in) | Initial Lumens (lm) | Mean Lumens (lm) | Avg. Life (Hrs) | Color Temp (K) | CRI | UPC |
| Fluorescent Lamps - High Output (T5) | | | | | | | | | | | | |
| 24 | T5 | Mini Bi-Pin | 4115 | FL24/T5/830/H0 | 25 | 21.61 | 2000 | 1880 | 20000 | 3000 | 85 | 844366041150 |
| 24 | T5 | Mini Bi-Pin | 4116 | FL24/T5/835/H0 | 25 | 21.61 | 2000 | 1880 | 20000 | 3500 | 85 | 844366041167 |
| 24 | T5 | Mini Bi-Pin | 4117 | FL24/T5/841/H0 | 25 | 21.61 | 2000 | 1880 | 20000 | 4100 | 85 | 844366041174 |
| 24 | T5 | Mini Bi-Pin | 4118 | FL24/T5/850/H0 | 25 | 21.61 | 2000 | 1880 | 20000 | 5000 | 85 | 844366041181 |
| 24 | T5 | Mini Bi-Pin | 4119 | FL24/T5/865/H0 | 25 | 21.61 | 2000 | 1880 | 20000 | 6500 | 85 | 844366041198 |
| 39 | T5 | Mini Bi-Pin | 4120 | FL39/T5/830/H0 | 25 | 33.39 | 4900 | 4606 | 20000 | 3000 | 85 | 844366041204 |
| 39 | T5 | Mini Bi-Pin | 4121 | FL39/T5/835/H0 | 25 | 33.39 | 4900 | 4606 | 20000 | 3500 | 85 | 844366041211 |
| 39 | T5 | Mini Bi-Pin | 4122 | FL39/T5/841/H0 | 25 | 33.39 | 4900 | 4606 | 20000 | 4100 | 85 | 844366041228 |
| 39 | T5 | Mini Bi-Pin | 4123 | FL39/T5/850/H0 | 25 | 33.39 | 4900 | 4606 | 20000 | 5000 | 85 | 844366041235 |
| 39 | T5 | Mini Bi-Pin | 4124 | FL39/T5/865/H0 | 25 | 33.39 | 4900 | 4606 | 20000 | 6500 | 85 | 844366041242 |
| 54 | T5 | Mini Bi-Pin | 4125 | FL54/T5/830/H0 | 25 | 45.2 | 5000 | 4700 | 20000 | 3000 | 85 | 844366041259 |
| 54 | T5 | Mini Bi-Pin | 4126 | FL54/T5/835/H0 | 25 | 45.2 | 5000 | 4700 | 20000 | 3500 | 85 | 844366041266 |
| 54 | T5 | Mini Bi-Pin | 4127 | FL54/T5/841/H0 | 25 | 45.2 | 5000 | 4700 | 20000 | 4100 | 85 | 844366041273 |
| 54 | T5 | Mini Bi-Pin | 4128 | FL54/T5/850/H0 | 25 | 45.2 | 5000 | 4700 | 20000 | 5000 | 85 | 844366041280 |
| 54 | T5 | Mini Bi-Pin | 4129 | FL54/T5/865/H0 | 25 | 45.2 | 5000 | 4700 | 20000 | 6500 | 85 | 844366041297 |
| 80 | T5 | Mini Bi-Pin | 4135 | * FL80/T5/830/H0 | 25 | 57.09 | 7000 | 6580 | 20000 | 3000 | 85 | 844366041358 |
| 80 | T5 | Mini Bi-Pin | 4136 | * FL80/T5/835/H0 | 25 | 57.09 | 7000 | 6580 | 20000 | 3500 | 85 | 844366041365 |
| 80 | T5 | Mini Bi-Pin | 4137 | * FL80/T5/841/H0 | 25 | 57.09 | 7000 | 6580 | 20000 | 4100 | 85 | 844366041372 |
| 80 | T5 | Mini Bi-Pin | 4138 | * FL80/T5/850/H0 | 25 | 57.09 | 7000 | 6580 | 20000 | 5000 | 85 | 844366041389 |
| 80 | T5 | Mini Bi-Pin | 4139 | * FL80/T5/865/H0 | 25 | 57.09 | 7000 | 6580 | 20000 | 6500 | 85 | 844366041396 |

***Items only available for special orders**