



→ HİDROLİK HORTUMLAR

HİDROLİK HORTUMLAR

FLEXOR 1SN – R1AT (HF)

SAE 100 R1AT- EN 853 1SN-DIN 20022 1SN



Stok Kodu	ANMA ÇAPı			DIŞ ÇAP		ÇALIŞMA BASINCI		PATLAMA BASINCI		BÜKME YARIÇAPı		kg/m	FİYAT Euro/m
	Size	mm	in	mm	in	Bar	psi	Bar	psi	mm	in		
1001330	-3	5	3/16	11,40	0,45	250	3630	1000	14520	90	3,60	0,18	3,16
1001331	-4	6	1/4	13,00	0,51	225	3270	900	13080	100	4,00	0,22	3,16
1001332	-5	8	5/16	14,50	0,57	215	3120	860	12480	115	4,60	0,25	3,39
1001333	-6	10	3/8	17,20	0,68	180	2610	720	10460	130	5,20	0,32	3,65
1001334	-8	13	1/2	20,10	0,79	160	2320	640	9280	180	7,20	0,41	3,98
1001335	-10	16	5/8	23,10	0,91	130	1890	520	7560	200	8,00	0,50	4,62
1001336	-12	19	3/4	27,30	1,07	105	1530	420	6120	240	9,60	0,61	6,13
1001337	-16	25	1	35,20	1,39	88	1280	352	5120	300	12,00	0,91	8,68
1001338	-20	32	1 1/4	42,50	1,67	63	920	252	3680	420	16,80	1,18	12,08
1001339	-24	38	1 1/2	49,70	1,96	50	730	200	2920	500	20,00	1,46	15,73
1001340	-32	51	2	62,90	2,48	40	580	160	2320	630	25,20	1,98	20,42

Çalışma sıcaklığı: -40°C–100°C

Kangal Boyu: 1"e kadar muhtelif boylarda, 1 ¼" üzeri max 40 m

FLEXOR 2SN – R2AT (HF)

SAE 100 R2AT- EN 853 2SN-DIN 20022-2SN



Stok Kodu	ANMA ÇAPı			DIŞ ÇAP		ÇALIŞMA BASINCI		PATLAMA BASINCI		BÜKME YARIÇAPı		kg/m	FİYAT Euro/m
	Size	mm	in	mm	in	Bar	psi	Bar	psi	mm	in		
1001341	-3	5	3/16	13,00	0,51	420	6000	1680	24000	90	3,60	0,28	3,60
1001342	-4	6	1/4	14,50	0,57	400	5800	1600	23200	100	4,00	0,35	3,55
1001343	-5	8	5/16	16,10	0,63	350	5000	1400	20000	115	4,60	0,41	3,67
1001344	-6	10	3/8	18,50	0,73	330	4800	1320	19200	125	5,00	0,49	4,18
1001345	-8	13	1/2	21,40	0,84	275	4000	1100	16000	175	7,00	0,62	4,65
1001346	-10	16	5/8	24,60	0,97	250	3630	1000	14520	200	8,00	0,72	5,90
1001347	-12	19	3/4	29,00	1,14	215	3120	860	12480	240	9,60	0,90	7,10
1001348	-16	25	1	36,80	1,45	165	2400	660	9600	300	12,00	1,28	10,35
1001349	-20	32	1 1/4	46,40	1,83	125	1820	500	7280	420	16,80	1,86	17,26
1001350	-24	38	1 1/2	53,70	2,11	90	1310	360	5240	500	20,00	2,37	21,95
1001351	-32	51	2	65,90	2,59	80	1160	320	4640	630	25,20	2,92	27,95

Çalışma sıcaklığı: -40°C–100°C

Kangal Boyu: 1"e kadar muhtelif boylarda, 1 ¼" üzeri max 40 m

FLEXOR R4 – 604

SAE 100 R4 Emiş Hortumu



Stok Kodu	ANMA ÇAPı			DIŞ ÇAP		ÇALIŞMA BASINCI		PATLAMA BASINCI		BÜKME YARIÇAPı		kg/m	FİYAT Euro/m
	Size	mm	in	mm	in	Bar	psi	Bar	psi	mm	in		
1000488	-20	32	1 1/4	42,00	1,65	14	200	56	800	96	3,78	0,89	20,40
1000489	-24	38	1 1/2	48,00	1,89	10	150	40	600	114	4,48	1,03	27,60
1000490	-32	51	2	61,00	2,40	7	100	28	400	153	6,02	1,32	29,20
1000491	-40	63	2 1/2	75,00	2,95	4	60	16	248	189	7,44	2,07	39,50
1000492	-48	76	3	88,00	3,46	4	60	16	248	228	8,98	2,47	51,50

Çalışma sıcaklığı: -40°C–100°C

Kangal Boyu: Max. 61 m

HİDROLİK HORTUMLAR

FLEXOR 4SP – MINETUFF

SAE 100 R10- EN 856 4SP



Stok Kodu	ANMA ÇAPI			DIŞ ÇAP		ÇALIŞMA BASINCI		PATLAMA BASINCI		BÜKME YARIÇAPI		kg/m	FİYAT
	Size	mm	in	mm	in	Bar	psi	Bar	psi	mm	in		
1000238	-8	13	1/2	24,60	0,97	415	6000	1660	24000	230	9,20	0,88	11,19
1000239	-10	16	5/8	28,20	1,11	350	5000	1400	20000	250	10,00	1,05	12,36
1000240	-12	19	3/4	32,20	1,27	380	4510	1520	22040	300	12,00	1,44	14,50
1000241	-16	25	1	39,70	1,56	320	4640	1280	18560	340	13,60	1,96	17,30

Çalışma sıcaklığı: -40°C–100°C

Kangal Boyu: 1"e kadar muhtelif boylarda

FLEXOR 4SH – MINETUFF

EN 856 4SH



Stok Kodu	ANMA ÇAPI			DIŞ ÇAP		ÇALIŞMA BASINCI		PATLAMA BASINCI		BÜKME YARIÇAPI		kg/m	FİYAT
	Size	mm	in	mm	in	Bar	psi	Bar	psi	mm	in		
1000245	-12	19	3/4	32,20	1,27	420	6000	1680	24000	280	11,20	1,57	15,60
1000246	-16	25	1	38,70	1,52	380	5500	1520	22000	340	13,60	1,95	20,30
1000247	-20	32	1 1/4	45,50	1,79	350	5000	1400	20000	460	18,40	2,47	26,73
1000248	-24	38	1 1/2	53,50	2,11	290	4200	1160	16800	560	22,40	3,27	37,50
1000249	-32	51	2	68,10	2,68	250	3650	1100	14600	700	28,00	4,67	50,15

Çalışma sıcaklığı: -40°C–100°C

Kangal Boyu: 1"e kadar muhtelif boylarda, 1 1/4" üzeri max 40 m

FLEXOR R13 – MINETUFF

SAE 100 R13- EN 856 R13



Stok Kodu	ANMA ÇAPI			DIŞ ÇAP		ÇALIŞMA BASINCI		PATLAMA BASINCI		BÜKME YARIÇAPI		kg/m	FİYAT
	Size	mm	in	mm	in	Bar	psi	Bar	psi	mm	in		
1000230-4S	-12	19	3/4	32,10	1,26	350	5000	1400	20000	241	9,60	1,60	20,30
1000231-4S	-16	25	1	38,70	1,52	380	5500	1520	22000	305	12,20	2,00	26,50
1000232-6S	-20	32	1 1/4	49,80	1,96	350	5000	1400	20000	419	16,80	3,60	40,10
1000233-6S	-24	38	1 1/2	57,30	2,26	350	5000	1400	20000	508	20,30	4,80	57,00
1000234-6S	-32	51	2	70,90	2,79	350	5000	1400	20000	635	25,40	6,60	77,80

Çalışma sıcaklığı: -40°C–121°C

Kangal Boyu: 1"e kadar muhtelif boylarda, 1 1/4" üzeri max 40 m

TEKNOSER Hidrolik Mühendislik Otomasyon San. Tic. Ltd. Şti.

MERKEZ

Mescit Mah. Adatepe Cad. Akın İş Merkezi No:7/A D:2

34 956 Orhanlı-Tuzla-/İSTANBUL

Tel: (216) 394 89 65-66

Fax: (216) 394 89 67

Tel: (532) 453 52 09

KOCAELİ ŞUBE:

Yenişehir Mah. Atayurt Cd No:4/B

41050 İzmit/Kocaeli

Tel: 0 532 453 52 42

