



## TECCARE

### TECHNICAL SPECIFICATIONS

	Metric	Imperial
Total gauge	4.5 mm	0.178"
Plank gauge	3.0 mm	0.118"
Underlayment gauge	1.5 mm	0.060"
Plank dimensions	152 mm x 915 mm	6" x 36"
Underlayment dimensions for the planks	305 mm x 915 mm	12" x 36"
Tile dimensions	457 mm x 457 mm	18" x 18"
Underlayment dimensions for the tiles	457 mm x 457 mm	18" x 18"
Wear Layer Thickness	0.3 mm (0.012")	
ASTM E 648 – Critical Radiant Flux CRF (W/cm <sup>2</sup> )	> 0.45	
ASTM E 662 – Smoke Density	≤ 450	
ASTM E 989 / E 492 – Sound Absorption	IIC 59	
ASTM F 925 – Chemical Resistance	Exceeds	
ASTM F 970 – Static Load (modified at 2,500 psi)	≤ 0.005"	
ASTM F 1514 – Heat Stability (ΔE ≤ 8.0)	Pass	
ASTM F 1515 – Light Stability (ΔE ≤ 8.0)	Pass	
ASTM F 1700 – Solid Vinyl Floor Tile	Class III, Type A or B	
ASTM F 1914 – Indentation	Residual ≤ 8%	
ASTM F 2055 – Squareness	0.010" maximum	
Indoor Air Quality (IAQ): Volatile Organic Compounds (VOC's)	FloorScore Certified by SCS Certification Registration Number SCS-FS-03325	
Maintenance	Very low	
PU (Polyurethane) surface treatment	Facilitates maintenance	
Limited Wear Warranty	10 years	

Please note that technical web site documents prevail.

