

SUPER SPORT LT500 SPECIFICATIONS (USA)



THE TRAILER YOUR CAR WOULD CHOOSE	
DECK LENGTH	DECK WIDTH
16' 5"	81"
OVERALL LENGTH	OVERALL WIDTH
21'	102"
FENDER HEIGHT Fender on 9" Fender off 7"	GROUND CLEARANCE 16" from deck
G.V.W.R.	G.A.W.R. (each axle)
7,000lbs	3,500lbs
TARE WEIGHT	LOAD CAPACITY
1,313lbs	5,678lbs
DECK ANGLE	FLARED TAIL WIDTH
Only 3-degrees	86"
ENGINEERED TO BE EFFORTLESS	
REMOVABLE FENDERS	LICENCE PLATE BRACKET
Extruded aluminum, powder coated	Aluminum, fold up
TIE POINTS	RECOVERY WINCH
Continuous airline track and slotted chassis rail	12V electric with wireless remote
JACK	COUPLING
Center mount jack wheel, auto stow wheel	10,000 lbs, 2 5/16" Snap-on steel coupler
WHEELS	TIRES

SHIFTR 14" x 6" Alloy, 5" x 4.5"	185R 14C 8 ply light truck
AXLE (patented)	SUSPENSION
3,500 lbs galvanized steel torsion	Independent torsion arm (PU)
HUBS	BRAKES
3,500 lbs	10" electric
WINCH	RIGGING
12V electric winch with wireless remote control	Double braided ½ " UHMWPE synthetic rope
BATTERY 12V 30AH GEL deep cycle	LIGHTING Micro LED fender mounted clearance Recessed LED stop, tail, indicators Combined LED/reflector marker lights
CHARGING Onboard DC-DC connected to trailer plug aux pin and solar panel	ELECTRIC CONNECTOR 7-Way RV, flat pin trailer plug
BUILT TO LAST A LIFETIME	
FINISH - ALUMINUM PARTS	FINISH - STEEL PARTS
Silver anodizing and black powder coating	Hot dip galvanized
CHASSIS & TONGUE	DECK
Extruded aluminum 6005-T6	Extruded aluminum 6005-T6 interlocking
Extruded 6005-T6 C section	panels