



## LED 2FT T8 Universal

### FEATURES

- Type B single or Double Ended
- Plug & Play Dual Mode (Type A & B)
- Shatterproof Glass
- Low thermal decay & maintenance
- No mercury or UV
- 50,000 hours lifetime

### CONSTRUCTION:

Shatterproof glass body with PET film and soft light.

### OPTICAL SYSTEM:

Bridgelux or Samsung 2835 LED chips. 200 degree beam angle / 300 degree view angle

### ELECTRICAL:

Ballast compatible. Available as 100-277V input. Single end and double ended are all available which can be compatible with shunted or non-shunted sockets. -20C or 50C, -4F to 122F.

### INSTALLATION & MOUNTING:

Type B single or double ended. Plug & Play dual mode (Type A & B)

### WARRANTY:

5-Year limited warranty. Actual performance may differ as a result of end-user environment and application.

### SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Conference rooms
- Schools
- Supermarkets
- Factories
- Hospitals
- Office Buildings
- Airports

**Most Efficient TLED  
on the market!!!**

WATTS	CCT	LUMENS	LUMENS PER WATT	CRI	RETAIL	PSE or SCL or SnoPod INSTANT REBATE	COST AFTER DISCOUNTS
8.5W	4,000 K	1,150 LM	136 LM/W	80	\$17.88	-\$4.00	\$13.88
8.5W	5,000 K	1,150 LM	136 LM/W	80	\$17.88	-\$4.00	\$13.88

# Retrofit examples:

## Fluorescent T8

Length	Current Wattage	LED Wattage	Wattage Reduction	Percentage Saved
2 Foot	17W	8.5W	8.5W	50%
2 Foot	32W	8.5W	23.5W	73%

## Fluorescent T12

Length	Current Wattage	LED Wattage	Wattage Reduction	Percentage Saved
2 Foot	20W	8.5W	11.50W	57%
2 Foot	25W	8.5W	16.5W	66%



Contact us at 206.826.7000 or visit us online at [www.LEDtoGO.us](http://www.LEDtoGO.us) for more information

