



LED 2FT T8 U-Shaped Universal

FEATURES

- Plug & Play Dual Mode (Type A & B)
- Shatterproof Glass
- Low thermal decay & maintenance
- No mercury or UV
- 50,000 hours lifetime

CONSTRUCTION:

Shatterproof glass body with Frosted lens and G13

OPTICAL SYSTEM:

Hongli 2835 LED chips. 180 degree beam angle.

ELECTRICAL:

Ballast compatible. Available as 120-277V input. Single end and double ended are all available which can be compatible with shunted or non-shunted sockets. -20C or 50C, -4F to 122F.

INSTALLATION & MOUNTING:

Type B single or double ended. Plug & Play dual mode (Type A & B)

WARRANTY:

5-Year limited warranty. Actual performance may differ as a result of end-user environment and application.

SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Conference rooms
- Schools
- Supermarkets
- Factories
- Hospitals
- Office Buildings
- Airports



WATTS	CCT	LUMENS	LUMENS PER WATT	CRI	RETAIL	PSE or SCL or SnoPUD INSTANT REBATE	COST AFTER DISCOUNTS
13.5W	4,000 K	1,700 LM	126LM/W	83	\$27.17	-\$4.00	\$23.17
13.5W	5,000 K	1,700 LM	126LM/W	83	\$27.17	-\$4.00	\$23.17

Retrofit examples:

Fluorescent T8

Length	Current Wattage	LED Wattage	Wattage Reduction	Percentage Saved
2 Foot	32W	12W	20W	63%
2 Foot	32W	15W	17W	53%

Fluorescent T12

Length	Current Wattage	LED Wattage	Wattage Reduction	Percentage Saved
2 Foot	38W	12W	26W	68%
2 Foot	38W	15W	23W	61%



Contact us at 206.826.7000 or visit us online at www.LEDtoGO.us for more information

