



LED 4FT T5 Universal

FEATURES

- NSF approved
- IP20 Rated
- Type B single or Double Ended
- Plug & Play Dual Mode (Type A & B)
- Shatterproof Glass
- Low thermal decay & maintenance
- No mercury or UV
- 50,000 hours lifetime

Construction:

Shatterproof glass body with Frosted lens.

OPTICAL SYSTEM:

Hongli 2835 LED chips. 175 degree beam angle / 320 degree field angle

ELECTRICAL:

Ballast compatible. Available as 120-277V input. Single end and double ended are all available which can be compatible with shunted or non-shunted sockets. -20C or 50C, -4F to 122F.

INSTALLATION & MOUNTING:

Type B single or double ended. Plug & Play dual mode (Type A & B). G13 base.

WARRANTY:

5-Year limited warranty. Actual performance may differ as a result of end-user environment and application.

SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Conference rooms
- Schools
- Supermarkets
- Factories
- Hospitals
- Office Buildings
- Airports



WATTS	CCT	LUMENS	LUMENS PER WATT	CRI	RETAIL	PSE or SCL or Sno Pud INSTANT REBATE	COST AFTER DISCOUNTS
24W	4,000 K	3,500 LM	127 LM/W	83	\$25.74	-\$4.00	\$21.74
24W	5,000 K	3,600 LM	131 LM/W	83	\$25.74	-\$4.00	\$21.74

Retrofit example:

Fluorescent T5

Length	Current Wattage	LED Wattage	Wattage Reduction	Percentage Saved
4 Foot	54W	24W	30W	56%



Contact us at 206.826.7000 or visit us online at www.LEDtoGO.us for more information

