



# Cisco Secure Network Server

---

# Contents

Product overview	3
Product specifications	3
Security applications	4
Ordering information	4
Connectors and LEDs	5
Form factor	5
Environmental	5
Regulatory standards	6
Cisco Capital	6
For more information	7

## Product overview

Granting and denying network access has evolved beyond simple user name and password verifications. Today, additional attributes related to users and their devices are used as decision criteria in determining authorized network access. Additionally, network service provisioning can be based on data such as the type of device accessing the network, including whether it is a corporate or personal device.

The Cisco® Secure Network Server is a scalable solution that helps network administrators meet complex network access control demands by managing the many different operations that can place heavy loads on applications and servers, including:

- Authorization and authentication requests
- Queries to identity stores such as Active Directory and LDAP databases
- Device profiling and posture checking
- Enforcement actions to remove devices from the network
- Reporting

The Cisco® Secure Network Server is based on the Cisco UCS® C220 Rack Server and is configured specifically to support the Cisco Identity Services Engine (ISE) security application. The Secure Network Server supports these applications in five versions. The Cisco Secure Network Server 3615 is designed for small deployments. The Secure Network Server 3655 and 3695 have several redundant components such as hard disks and power supplies, making it suitable for larger deployments that require highly reliable system configurations.

Figure 1 shows the Cisco Secure Network Server.



**Figure 1.**  
Cisco SNS-3615, SNS-3655, and SNS-3695 Secure Network Server

## Product specifications

Table 1 lists specifications of the Cisco Secure Network Server.

**Table 1.** Product specifications

Product Name	Secure Network Server 3615	Secure Network Server 3655	Secure Network Server 3695
<b>Processor</b>	1 - Intel Xeon 2.10 GHz 4110	1 - Intel Xeon 2.10 GHz 4116	1 - Intel Xeon 2.10 GHz 4116
<b>Cores per processor</b>	8	12	12
<b>Memory</b>	32 GB (2 x 16 GB)	96 GB (6 x 16 GB)	256 GB (8 x 32 GB)
<b>Hard Disk</b>	1 - 2.5-in. 600-GB 6Gb SAS 10K RPM	4 - 2.5-in. 600-GB 6Gb SAS 10K RPM	8 - 2.5-in. 600-GB 6Gb SAS 10K RPM

Product Name	Secure Network Server 3615	Secure Network Server 3655	Secure Network Server 3695
Hardware RAID	No	Level 10 Cisco 12G SAS Modular RAID Controller	Level 10 Cisco 12G SAS Modular RAID Controller
Network Interfaces	2 X 10Gbase-T 4 x 1GBase-T	2 X 10Gbase-T 4 x 1GBase-T	2 X 10Gbase-T 4 x 1GBase-T
Power Supplies	1 x 770W	2 x 770W	2 x 770W

## Security applications

The Cisco Secure Network Server supports Cisco's powerful network access and control security applications:

### Cisco Identity Services Engine

An integral component to Cisco's cybersecurity initiative, the Cisco Identity Services Engine (ISE) is a revolutionary product that extends the network access and admission control capabilities first offered in Cisco NAC and Cisco Secure ACS. Looking beyond user name and password, the Identity Services Engine delivers unprecedented abilities to acquire user and device identity and context information to forge flexible and powerful policies that govern authorized network access. ISE is an all-in-one enterprise policy control platform that can reliably provide secure access for wired, wireless and VPN networks. ISE can also help IT with secure BYOD on-boarding and allow IT to provide differentiated Guest Access. The Identity Services Engine provides enforcement actions that allow administrators to restrict devices from the network that are violating access and policies.

Table 2 lists ISE endpoint scalability metrics for the Secure Network Servers.

**Table 2.** Identity Services Engine deployment scalability (ISE 2.4 and Greater)

	Secure Network Server 3615	Secure Network Server 3655	Secure Network Server 3695
Endpoints supported in a standalone configuration	10,000	25,000	50,000
Endpoints supported per Policy Services Node	10,000	50,000	100,000

## Ordering information

Table 3 lists ordering information for the Cisco Secure Network Servers.

**Table 3.** Product ordering information

Server Part Numbers	Server Description
SNS-3615-K9	Secure Network Server for ISE applications (small)
SNS-3655-K9	Secure Network Server for ISE applications (medium)
SNS-3695-K9	Secure Network Server for ISE applications (large)

Table 4 lists the Secure Network Server component spares that can be used as Field Replaceable Units (FRUs).

**Table 4.** Spare components for the Cisco Secure Network Server

Secure Network Server	Component Part Number	Component Description
3615/3655/3695	UCS-HD600G10K12N	600-GB 12-Gb SAS 10K RPM SFF hard disk; hot pluggable; drive sled mounted
3615/3655/3695	UCSC-PSU1-770W=	770W power supply
3615/3655/3695	N20-BKVM=	KVM cable
3615/3655/3695	UCSC-RAILB-M4=	Rail kit

## Connectors and LEDs

Table 5 lists Connectors and LEDs on the Cisco SNS-3615, SNS-3655, and SNS-3695 Secure Network Servers.

**Table 5.** SNS-3615, SNS-3655, and SNS-3695 Connectors and LEDs

Connector/LEDs	Description
Front-panel connector	One KVM console connector (supplies 2 USB, 1 VGA, and 1 serial connector)
Front-panel locator LEDs	Power status, fan status, system status, power supply status, unit identification, and network link activity
Additional rear connectors	Additional interfaces, including a VGA video port, 2 USB ports, an RJ-45 serial port, 1 Gigabit Ethernet management port, and dual 10 Gigabit Ethernet ports

## Form factor

**Physical dimensions (H x W x D)** 1RU: 1.7 x 16.9 x 29.8 in. (4.32 x 43 x 75.6 cm).

## Environmental

Table 6 lists environmental information for the Cisco Secure Network Servers.

**Table 6.** Regulatory standards compliance: Safety and EMC

Item	Specification
Temperature: Operating	41 to 95° F (5 to 35° C) (operating, sea level, no fan fail, no CPU throttling, turbo mode)
Temperature: Nonoperating	-40 to 149° F (-40 to 65° C)
Humidity: Operating	10 to 90% noncondensing
Humidity: Nonoperating	5 to 93% noncondensing
Altitude: Operating	0 to 10,000 ft (0 to 3000m); maximum ambient temperature decreases by 1° C per 1000 ft

Item	Specification
Altitude: Nonoperating	0 to 40,000 ft (12,000m)
Heat Dissipation	Approximately 2500 BTU/h

## Regulatory standards

Table 7 lists regulatory standards compliance information for the Cisco Secure Network Servers.

**Table 7.** Regulatory standards compliance: Safety and EMC

Specification	Description
<b>Safety</b>	<ul style="list-style-type: none"> <li>• UL 60950-1 No. 21CFR1040 Second Edition</li> <li>• CAN/CSA-C22.2 No. 60950-1 Second Edition</li> <li>• IEC 60950-1 Second Edition</li> <li>• EN 60950-1 Second Edition</li> <li>• IEC 60950-1 Second Edition</li> <li>• AS/NZS 60950-1</li> <li>• GB4943 2001</li> </ul>
<b>EMC: Emissions</b>	<ul style="list-style-type: none"> <li>• 47CFR Part 15 (CFR 47) Class A</li> <li>• AS/NZS CISPR22 Class A</li> <li>• CISPR2 2 Class A</li> <li>• EN55022 Class A</li> <li>• ICES003 Class A</li> <li>• VCCI Class A</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> <li>• KN22 Class A</li> <li>• CNS13438 Class A</li> </ul>
<b>EMC: Immunity</b>	<ul style="list-style-type: none"> <li>• EN55024</li> <li>• CISPR24</li> <li>• EN300386</li> <li>• KN24 (SNS-3515 and SNS-3595)</li> <li>• KN35 (SNS-3615, SNS-3655, and SNS-3695)</li> </ul>

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments.

[Learn more.](#)

---

## For more information

For more information, please visit the following resources:

- Cisco Identity Services Engine: <https://www.cisco.com/go/ISE>
- Cisco UCS Servers: <https://www.cisco.com/go/unifiedcomputing>

## How to buy

To view buying options and speak with a Cisco sales representative, visit [www.cisco.com/c/en/us/buy](http://www.cisco.com/c/en/us/buy).

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)