JET SKI® STX® 160









POWER

Engine 4-stroke, DOHC, four valves per cylinder, 4-

cylinder inline

Displacement 1,498cc

Bore x Stroke 83.0 x 69.2mm

Compression

Ratio

10.6:1

Induction Naturally aspirated

Maximum Boost N/A

Cooling System Inducted water

Fuel System DFI® with 60mm throttle body

Ignition TCBI with Digital Advance

Starting System Electric

Propulsion System

148mm jet pump, axial-flow, single stage

Impeller 3-blade, oval-edge stainless steel

Coupling	Direct drive from engine
Coupling	Direct drive from engine

Oil Capacity 5.3 qt

Fuel Capacity 20.6 gal

Load Capacity 496 lb

Storage Capacity 35.0 gal

DETAILS

Overall Length 124.1 in

Overall Width 46.5 in

Overall Height 45.4 in

Curb Weight 864.4 lb*

Seating Capacity 3

Protection Plus™ (optional)

Color Choices Crystal White/Vibrant Blue

Warranty 12 Month Limited Warranty

Kawasaki 12, 24, 36, or 48 months

PERFORMANCE

Lubrication Semi-dry sump system

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2023 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.





