igloo linear





Dimension Drawings





Overview

iGLOO is a digitally controlled recessed linear luminaire with with unrivalled output and power. iGLOO delivers up to 4750 lumens at over 100 lumens per Watt and has outstanding flexibility with digital control via Casambi wireless or Dali control. Multiple length variants are available, from 300mm to 120mm, and if higher or lower output performance is required, solutions can be provided.


The product is designed for application into high end retail displays, or cabinet lighting allowing designers great power and punch fromm a small luminaire.


Features

- Minimalist fully integrated linear with multiple control options including casambi
- Exceptional power per metre from a compact light source
- Delivering 4750 or 3600 lumens per metre at over 100 Lumens per Watt

Options


- Choice of output with bespoke outputs on request.
- Casambi or Dali contrl as standard DMX also an option
- Narrow and wide beam options available
- Choice of 2700, 3000, 4000K
- Black, white and RAL paint finish options.






Luminaire specification

Mounting	Surface Suspendend or Trecessed						
Module Size	300, 600, 1200mm						
Body Material	Extruded & Machined Aluminium						
Finish	Matt Powder Coat						
IP Rating	IP20						
Weight	0.2kg						
Warranty	5 Years						











Luminaire part code

Part	Finish	Code	Mounting	Code	Luminaire Length (mm)	Notes								
iGLOO	BLACK	BL	SURFACE	SURF	300									
	WHITE	WH		TK48	600									
	RAL	RA	RECESSED	REC	1200									
						Module	ule part code							
						iGLOO	90+ CRI / 100+ Lumens pw							
						Output (lumens pm)	Colour Temp	Colour Code	Beam	Degres	Control	Code		
						4750 EB	2700	27	15	15	DALI	DA		
	1					3600 SB	3000	30	24	24	CASAMBI	CA		
							4000	40			DMX	DM		

iGloo part code generation

	1	Finish	1	Mounting	/	Luminaire Length	1	Output	Colour Temp	1	Beam	1	Control
iGLOO	/	BL	/	SURF	/	300	1	EB	27	/	24	/	DA





