

IGLOO S2400



Like all other Epoke machines, IGLOO features surface treatment consisting of sandblasting, zinc dust priming, 2-component polyurethane base coat and a 2-component top coat. The spreading disc and feed funnel are made of stainless steel.

Standard Features:

- Standard profiled conveyor belt
- Adjustable load relief plate above conveyor
- SH- operation by vehicle hydraulics - Dealer to supply hydraulic hoses
- Spreading disc with short funnel
- Safety grate
- Standard distribution box ground speed adapter
- Computer control system EpoBasic remote control system

Options for 0.8 m3 Igloo:

- 0.15 m3 hopper extension (0.95 m3 total capacity)
- 0.3 m3 hopper extension (1.1 m3 total capacity)
- 30% prewetting system with 2 X 170L (340L total) side tanks, liquid empty sensor, auto stop fill and shut off valve

Options for 1.1 m3 Igloo:

- 608019 0.3 m3 hopper extension (1.4 m3 total capacity)
- 605108 0.5 m3 hopper extension (1.6 m3 total capacity)
- 30% prewetting system with 2 X 170L (340L total) side tanks, liquid empty sensor, auto stop fill and shut off valve

Options for 1.4 m3 Igloo:

- 606491 0.2 m3 hopper extension (1.6 m3 total capacity)
- 605109 0.6 m3 hopper extension (2.0 m3 total capacity)
- 30% prewetting system with 2 X 170L (340L total) side tanks, liquid empty sensor, auto stop fill and shut off valve

Options (Available for all Igloo S2300 Hopper sizes):

- Lighting package with work light and rotating beacon
- Electric symmetry
- GPS receiver including antenna
- Proximity sensor for two plows
- EpoMaster III and large distribution box
- Off loading system includes lateral guides
- Gasoline engine (Honda 9 HP- electric start controlled from EpoBasic/ EpoMaster).
- Folding cover