

S3800 Sirius



(driven by truck mounted hydraulic system) with the following standard features and included options:

Standard Features:

- stainless steel agitator with replaceable steel spring fingers
- stainless steel delivery roller with 8mm steel cams
- soft rubber base standard spring base and spring base adjustment
- conveyor belt
- galvanized feed funnel and inspection ladder
- central placed grease points
- hydraulic fittings JIC – 12 pressure return- Dealer to supply hydraulic hoses
- large distribution box with RS232
- EpoMaster III controller with RS232 card reader
- ground speed adapter
- spout, stainless steel
- wiring only for work light and wiring and beacon stems for two beacons- lights to be Dealer supplied installed
- hydraulic pressure gauge in machine house
- neutral gear
- liquid system including side tanks
- 5 – 30% variable prewetting system
- shut off valve
- stainless steel liquid spout
- safety grate 4" X 4" with 8 degree slope

Options:

- Front tank (1000 L) 265 gallon
- Liquid level indicator
- Auto-stop of liquid filling
- Leg system (includes the following): 17 ton brackets; rubber protection bars on subframe; side marker/ flag; spring assist for rear legs; short console frame for front roller; multiplug kit;
- lateral guides
- Folding cover
- 'D' ring tie down kit- Dealer installed for 4 points at top corner of hopper/extension
- Electric symmetry
- Level indicator for dry material
- Spring base quick release
- EpoTector
- Air temperature sensor
- Proximity sensor for two plows