

Contractor Dump Bodies Medium & Heavy Duty



FEATURES & SPECIFICATIONS

- 12 gauge HSLAS grade 50 steel sides on fold down side bodies.
- 10 gauge double wall sides on 14 foot fixed side body.
- 7 gauge floor, standard on 14' and 16', optional on 12'.
- 17" side height with brackets for sideboard extensions.
- LED lighting standard
- Fully boxed dirt shedding top rails.
- 45 degree sloped rub rails.
- Four vertical side braces per side.
- Full depth boxed rear corner posts with concealed hardware for a clean, streamlined look.
- Front panel includes a triple bend horizontal top rail.
- 7" structural channel long sills and 3" i-beam cross sills on 12" centers.
- Rugby products' lighting locations have been designed to assist the installer in meeting FMVSS / CMVSS 108 requirements.
- All appearance corners have radius bends.
- 2 part epoxy primer.
- ½ cab shield.

FEATURES & SPECIFICATIONS ON FOLD DOWN SIDE BODY

- Independently operated double door sides with removable center post.
- Single pin release system to quickly remove center post.
- Each side door features centrally located quick release lever.
- 2 or 3 heavy duty double strap greaseable hinges per door.

TAILGATE FEATURES & SPECIFICATIONS

- Tailgate sloped 10 degree inward.
- New oval shaped stop/turn/tail light in rear corner posts.
- EZ - LATCH™ upper hardware on tailgate. (patented)
- 23" end height, four-way tailgate with adjustable rod on trip lever.
- 10 gauge fully boxed tailgate frame with two vertical braces.
- Reinforced decking edge at rear of the body.
- 1 ¼" diameter top and 1" bottom hinge pins.

OPTIONS INCLUDE

- Coal chute door
- Spreader Apron