



## Articulating Cranes <15.5tm

Not only can IMT knuckleboom cranes easily load and unload materials, even when the work site is full of obstacles — they can stow within themselves, freeing up payload space for additional materials. We offer cranes that are ideal for virtually any project — with capacities at minimum reach ranging from 905 lb - 6300 lb (410 kg - 2860 kg).

Model	Maximum Crane Rating	Maximum Lift Capacity	Maximum Horizontal Reach	Maximum Horizontal Reach Capacity
<a href="#">2.5/18</a>	18,085 ft-lb (2.5 tm)	1740 lb (790 kg)	23' (7 m)	715 lb (325 kg)
<a href="#">3.2/23</a>	23,145 ft-lb (3.2 tm)	2195 lb (995 kg)	23' 7" (7.2 m)	960 lb (435 kg)
<a href="#">610K-MCS/RC</a>	39,370 ft-lb (6 tm)	6,526 lb (2960 kg)	35' 4" (10.8 m)	948 lb (430 kg)
<a href="#">610K-MC</a>	39,771 ft-lb (5.5 tm)	5,986 lb (2715 kg)	35' 4" (10.8 m)	838 lb (380 kg)
<a href="#">710K-RCS</a>	45,180 ft-lb (6.3 tm)	6,746 lb (3060 kg)	35' 5" (10.8 m)	992 lb (450 kg)
<a href="#">810K-MC</a>	50,527 ft-lb (7 tm)	7,562 lb (3430 kg)	36' 1" (11 m)	1,135 lb (515 kg)
<a href="#">810K-MCS/RC</a>	54,858 ft-lb (7.6 tm)	3,163 lb (1435 kg)	36' 1" (11 m)	1,145 lb (575 kg)
<a href="#">910K-RCS</a>	57,745 ft-lb (8 tm)	8,509 lb (3860 kg)	36' 1" (11 m)	1,322 lb (600 kg)
<a href="#">9/65 SL</a>	65,100 ft-lb (9 tm)	8380 lb (3800 kg)	45' 11" (14. m)	950 lb (430 kg)
<a href="#">9/65 DL</a>	63,650 ft-lb (8.8 tm)	9040 lb (4100 kg)	45' 11" (14 m)	950 lb (430 kg)
<a href="#">10/72 SL</a>	72,330 ft-lb (10 tm)	9722 lb (4410 kg)	45' 11" (14 m)	1100 lb (500 kg)
<a href="#">10/72 DL</a>	70,160 ft-lb (9.7 tm)	10,384 lb (4710 kg)	45' 11" (14 m)	1060 lb (480 kg)

<a href="#"><u>11/78 SL</u></a>	77,395 ft-lb (10.7 tm)	9170 lb (4160 kg)	49' 3" (15 m)	1015 lb (460 kg)
<a href="#"><u>11/78 DL</u></a>	76,670 ft-lb (10.6 tm)	9280 lb (4210 kg)	49' 3" (15 m)	1015 lb (460 kg)
<a href="#"><u>12/86 SL</u></a>	86,075 ft-lb (11.9 tm)	10,626 lb (4820 kg)	49' 3" (15 m)	1215 lb (550 kg)
<a href="#"><u>12/86 DL</u></a>	84,625 ft-lb (11.7 tm)	10,670 lb (4840 kg)	49' 3" (15 m)	1190 lb (540 kg)
<a href="#"><u>13/88 SL</u></a>	88,245 ft-lb (12.2 tm)	9920 lb (4500 kg)	56' 5" (17.2 m)	750 lb (340 kg)
<a href="#"><u>13/88 DL</u></a>	87,520 ft-lb (12.1 tm)	10,780 lb (4890 kg)	56' 5" (17.2 m)	750 lb (340 kg)
<a href="#"><u>14/98 SL</u></a>	97,645 ft-lb (13.5 tm)	11,680 lb (5300 kg)	56' 5" (17.2 m)	925 lb (420 kg)
<a href="#"><u>14/98 DL</u></a>	97,645 ft-lb (13.5 tm)	12,275 lb (5570 kg)	56' 5" (17.2 m)	925 lb (420 kg)
<a href="#"><u>15/105 SL</u></a>	104,880 ft-lb (14.5 tm)	12,125 lb (5500 kg)	56' 5" (17.2 m)	1060 lb (480 kg)
<a href="#"><u>15/105 DL</u></a>	104,880 ft-lb (14.5 tm)	13,470 lb (6110 kg)	56' 5" (17.2 m)	1060 lb (480 kg)
<a href="#"><u>3000</u></a>	30,150 ft-lb (4.2 tm)	5,000 lb (2268 kg)	15' 0" (4.6 m)	1950 lb (885 kg)
<a href="#"><u>5217</u></a>	52,300 ft-lb (7.2 tm)	6900 lb (3130 kg)	17' 5" (5.3 m)	2950 lb (1340 kg)
<a href="#"><u>7415</u></a>	74,000 ft-lb (10.2 tm)	12,000 lb (5443 kg)	15' 1" (4.6 m)	4700 lb (2130 kg)



## Articulating Cranes >16tm

The perfect addition to most any job site, IMT knuckleboom cranes make loading and unloading easy, and range in capacity from 116,450 – 320,000 ft-lb (16.1 - 44.3 tm).

And since they can stow within themselves, they offer more payload space for additional materials.

Model	Maximum Crane Rating	Maximum Lift Capacity	Maximum Horizontal Reach	Maximum Horizontal Reach Capacity
<a href="#">17/117 SL</a>	116,450 ft lb (16.1 tm)	13,445 lb (6100 kg)	56' 5" (17.2 m)	1280 lb (580 kg)
<a href="#">17/117 DL</a>	115,730 ft lb (16.0 tm)	15,625 lb (7090 kg)	56' 5" (17.2 m)	1255 lb (570 kg)
<a href="#">18/124 SL</a>	119,345 ft lb (16.5 tm)	13,800 lb (6260 kg)	71' 2" (21.7 m)	615 lb (280 kg)
<a href="#">18/124 DL</a>	120,070 ft lb (16.6 tm)	14,265 lb (6470 kg)	71' 2" (21.7 m)	615 lb (280 kg)
<a href="#">20/138 SL</a>	133,085 ft lb (18.4 tm)	16,200 lb (7350 kg)	71' 2" (21.7 m)	815 lb (370 kg)
<a href="#">20/138 DL</a>	133,085 ft lb (18.4 tm)	16,265 lb (7380 kg)	71' 2" (21.7 m)	815 lb (370 kg)
<a href="#">22/153 SL</a>	148,275 ft lb (20.5 tm)	17,065 lb (7740 kg)	71' 2" (21.7 m)	880 lb (400 kg)
<a href="#">22/153 DL</a>	149,000 ft lb (20.6 tm)	17,550 lb (7960 kg)	71' 2" (21.7 m)	880 lb (400 kg)
<a href="#">26/180 SL</a>	164,910 ft lb (22.8 tm)	18,940 lb (8590 kg)	71' 2" (21.7 m)	1125 lb (510 kg)
<a href="#">26/180 DL</a>	165,635 ft lb (22.9 tm)	19,335 lb (8780 kg)	71' 2" (21.7 m)	1125 lb (510 kg)

<a href="#"><u>32/222</u></a>	222,050 ft lb (30.7 tm)	15,058 lb (6830 kg)	77' 10" (23.7 m)	1764 lb (800 kg)
<a href="#"><u>40/275</u></a>	274,855 ft-lb (38 tm)	19,025 lb (8630 kg)	79' (24.1 m)	2225 lb (1010 kg)
<a href="#"><u>50/345</u></a>	345,015 ft-lb (47.7 tm)	22,840 lb (10,360 kg)	78' 11" (24.1 m)	3085 lb (1400 kg)
<a href="#"><u>60/427</u></a>	409,390 ft lb (56.6 tm)	27,845 lb (12,630 kg)	67' 7" (20.6 m)	4210 lb (1910 kg)
<a href="#"><u>80/565</u></a>	516,440 ft lb (71.4 tm)	35,410 lb (16,060 kg)	76' 9" (23.4 m)	5645 lb (2560 kg)
<a href="#"><u>12916</u></a>	129,000 ft lb (17.8 tm)	14,000 lb (6350 kg)	16' 2" (4.9 m)	8000 lb (3630 kg)





## Hydraulic Loaders

Ideal for handling stacked or palletized material, IMT hydraulic wallboard loaders provide excellent lift capacity, extensive reach, precise maneuverability, and exceptional operator visibility — even in tight places.

Model	Horizontal Reach	Maximum Lift Capacity	Lifting Height
<a href="#">16000</a>	42' (12.8 m)	5825 lb (2642 kg)	54' 3" (16.5 m)
<a href="#">24562</a>	62' 3" (19 m)	5000 lb (2270 kg)	75' 6" (23 m)
<a href="#">28562</a>	62' 3" (19 m)	5700 lb (2585 kg)	71' 4" (21.8 m)





## Telescopic Cranes

All of our telescopic cranes feature cycle times designed for maximum productivity, a lifting capacity of 14,000 lb (6350 kg), a number of winch speeds, anti-two-block protection, overload shutdown systems, cylinder holding valves, and a tethered remote control. And because they're compact, they require minimal mounting space. You can choose 12-VDC power or PTO-driven hydraulics, which can also be equipped with radio remote controls.

Model	Crane Rating	Horizontal Reach	Maximum Lift Capacity
<a href="#"><u>.5/4</u></a>	3260 ft-lb (0.5 tm)	6' 6" (2.0 m)	950 lb (430 kg)
<a href="#"><u>3203i</u></a>	12,000 ft-lb (1.6 tm)	15' (4.6 m)	4000 lb (1815 kg)
<a href="#"><u>1015</u></a>	10,500 ft-lb (1.4 tm)	15' 0" (4.6 m)	3200 lb (1450 kg)
<a href="#"><u>1.5/10</u></a>	10,850 ft-lb (1.5 tm)	9' 8" (2.9 m)	2645 lb (1200 kg)
<a href="#"><u>4004i</u></a>	18,000 ft-lb (2.5 tm)	16' 0" (4.9 m)	4000 lb (1814 kg)
<a href="#"><u>2020</u></a>	20,000 ft-lb (2.8 tm)	20' 0" (6.1 m)	5000 lb (2268 kg)
<a href="#"><u>5005i</u></a>	30,000 ft-lb (4.1 tm)	20' 0" (6.1 m)	5000 lb (2268 kg)
<a href="#"><u>2820</u></a>	28,000 ft-lb (3.9 tm)	20' 6" (6.3 m)	5000 lb

			(2268 kg)
<a href="#"><u>6006i</u></a>	38,000 ft-lb (5.3 tm)	22' 0" (6.7 m)	6000 lb (2722 kg)
<a href="#"><u>6000</u></a>	39,000 ft-lb (6.7 tm)	22' 6" (6.9 m)	6000 lb (2721.6 kg)
<a href="#"><u>7500</u></a>	52,000 ft-lb (7.3 tm)	30' 10" (6.9 m)	7500 lb (3402 kg)
<a href="#"><u>8600</u></a>	60,000 ft-lb (8.4 tm)	30' 10" (9.4 m)	8600 lb (3901 kg)
<a href="#"><u>10000</u></a>	75,000 ft-lb (10.4 tm)	30' 10" (9.4 m)	10,000 lb (4535.9 kg)
<a href="#"><u>12000</u></a>	79,000 ft-lb (11.1 tm)	31' 0" (9.4 m)	12,000 lb (5443.1 kg)
<a href="#"><u>14000</u></a>	95,000 ft-lb (13.3 tm)	31' 0" (9.4 m)	14,000 lb (6350 kg)