

MNCU Series Network Controller

MNCU Series of Fanless Network Controller



The MNCU Series of Fanless Network Controller (NCU) supporting both Modbus IP and BACnet® IP Protocols. It also supports user logic programming via SIDE. There are over 40 types of programmable functions available, typically PID, scheduler, conversion, timer, utilities, totaliser and etc. Graphics and trending can be set up from the web browser (Selected models only).

Features

- Supports user logic programming via SIDE.
- Modbus and BACnet®, are supported on the same controller which provides flexibility for implementation.
- Passive cooling design with compact size
- Vesa mountable

Specifications

| Model Standard | MNCU-M | MNCU-B | MNCU-AG | MNCU-A5 | | |
|---------------------------------|--|--|-------------------------------|-------------------------------|--|--|
| Colour | | | | | | |
| Construction | Black High quality all aluminium | | | | | |
| CPU Memory | Quad Core A55 2.0GHz | Intel Celeron | Intel N100 | Intel i5 | | |
| | LPDDR4 4GB 32GB | | 4 ~ 8 GB | ' | | |
| Storage | (14GB for System) | 128GB/512GB (14GB for System) | | | | |
| System I/O | 1 x HDMI 1 x Gigabit Ethernet Port 2 x 2.5Gbps Ethernet Port 2 x USB 3.0 | Einernei Pori Z X USB | 2 x HDMI | | | |
| Power Supply | USB-C, support PD, 5/9/12V | 1 x Power switch AC 100-240V,60Wadapter | AC 100-240V, 48/60W adapter | AC 100-240V, 90W adapter | | |
| Operating | 0°C ~+60°C | | | | | |
| Temperature | 0 € ~+00 € | | | | | |
| Humidity | | 5% ~ 90% relative humidity, non-condensing | | | | |
| Dimensions | 94.5 x 68 x 30mm | 136 x 127 x 40mm | 150 x 126.5 x 45mm | 170 * 140 * 58 mm | | |
| Weight | 0.264kg | 0.65kg | 0.84kg | 1.1kg | | |
| Certification | CCC | ccc | CE, CCC, FCC Class A, RoHS | CE, CCC, FCC Class A, RoHS | | |
| Max no of users | 5 | 10 | 20 | 50 | | |
| Max no of user permission group | 2 | 5 | 5 | 5 | | |
| No of Concurrent users | 1 | 3 | 5 | 10 | | |



MNCU Series Network Controller

| Max no of Graphical pages | 20 | 100 | 250 | 390 | |
|------------------------------|--|--|------|------|--|
| Max no of points | 250 (UI & programming) 5000 (Programming only) | 800 (UI & programming) 6000 (Programming only) | 1200 | 1800 | |
| Max no of points/schedule | 10 | | | | |
| Min trending interval | 10secs | | | | |

^{*}Specifications and certifications are based on options and may vary.

Packing List

1x Power Adapter

Ordering Guide

| Model | MNCU-M (Programming Only) MNCU-MW MNCU-B (Programming Only) MNCU-BW | 4 |
|---------|--|------------|
| RAM | MNCU-AG MNCU-A5 4GB DDR4 (N/A for MNCU-Mx) 8GB DDR4 (N/A for MNCU-Mx) | 8 |
| Storage | 128GB (N/A for MNCU-Mx) 512GB (N/A for MNCU-Mx) | 128 512 |