

UNFINISHED LIVE SAWN ENGINEERED FLOORING SPECIFICATIONS



SPECIE	WHITE OAK
GRADES	MIXED GRADE
GRAIN PATTERNS	LIVE SAWN
SURFACE	UNFINISHED
WIDTHS	6", 7" & 8"

LENGTHS	4'+ WITH 8' LENGTH AVERAGE 3'-10' WITH 5' LENGTH AVG
---------	---

*Please note our longer length options are not random length bundles. They are nested by lengths. Example: 4' length bundles, 5' length bundles etc.
GBF will try to ship as close to the square footage ordered as possible.
We could include up to 5% additional on long lengths which is considered a special custom order.
It is the installers responsibility to sort and mix the various lengths while racking out the floor.

THICKNESS	3/4" 4mm WEAR LAYER (Extremely stable in all stated/Approved NWFA installation guideline conditions)
-----------	---

WEAR SURFACE	STANDARD 5/32 or 4mm Material may require light screening or light sanding at jobsite. All wear layers are sawn veneers to give a solid look with dimensional stability Defects will be filled with black epoxy. May require additional filler during installation.
--------------	--

SUBSTRATE	PLY-CORE BY GRAF BROTHERS 3/4" thickness 13mm Vertical Grain Poplar center core, 2mm Aspen or Basswood Backer Board
-----------	--

MACHINING	Tongue & Groove and End Matched, Square Edged
-----------	---

STYLES	SINGLE PLANK
--------	--------------

INSTALLATION	Can be nailed, stapled, or glued. When gluing please follow NOFMA/NWFA recommendations Can be installed above, on or below grade. Not recommended for floating floor installation. Radiant Floor Systems: 4mm only. See sales rep for details.
--------------	--

INDIVIDUAL SPECIFICATIONS

WHITE OAK	MIXED GRADE	LIVE SAWN
-----------	-------------	-----------

GRADE SPECIFICATIONS

MIXED GRADE: Will contain a mix of all flooring grades within the product
Natural Defects will be filled with black epoxy. May require additional filler during installation.
Also available upon request without filler

See our www.grafbro.com for photos of grades

1.16.2025