



.Angle World LLC.
Manufacture & Trading Company
7924 State Road
Philadelphia, PA 19136
www.angleworld.com



5 December 2017

Description: Engineered Vinyl Plank with Attached EVA Underlayment (V-EVO™)

Warranty: Lifetime Limited Residential Wear Warranty; Lifetime Limited Structural Warranty; Lifetime Limited Waterproof Warranty; 10 Year Limited Commercial Wear Warranty

Installation: Float, Glue Down

Color: Sequoia

Size/Packaging: 5.1" x 47.91" x 7.5 mm Planks 15.3 sq. ft./carton, 8 planks per carton, 21 lbs. each carton, 84 ctns per pallet (1943 lbs)

Construction: 1.5 mm virgin PVC (0.5 mm/20 mil wear surface) 4 mm core (Limestone & virgin PVC Composite). 2 mm EVA underlayment

Wear Finish: 2 coats UV-cured acrylic Gloss Level: 5% - 8%

TEST DATA

ASTM-E648 Critical Radiant Flux: Meets or exceeds, Class 1

ASTM E492-09 Impact Sound Conduction: IIC 67 db

ASTM E90-09 Airborne Sound Conduction: STC 67 db

ASTM C518 Thermal Resistance: R Value – 0.6

NALFA 3.2 Thickness Swell: Class 4, Heavy Commercial

NALFA 3.3 Xenon Light Resistance: Class 4, Heavy Commercial

NALFA 3.4 Cleanability-Stain Resistance: Class 4, Heavy Commercial

NALFA 3.5 Large Ball Impact Resistance: Class 4, Heavy Commercial

NALFA 3.6 Small Ball Impact Resistance: Class 4, Heavy Commercial

NALFA 3.8 Dimensional Tolerance: Class 4, Heavy Commercial

NALFA 3.9 Caster Chair: Class 3, Commercial NALFA 3.10 Surface Bonding: 1.31 N/mm – Exceeds Class 3 Commercial Requirement

ASTM E303 Dynamic Coefficient of Friction: 0.35 DCOF (Wet slip resistance) Low Risk Classification

ASTM F-970-07 Static Load Limit: 0.004 inch – Passes at 250 psi

ASTM-F2753 Rolling Load Over Resilient FC: 0.024 inch

ASTM F 1514 Color Resistance to Heat: Meets <8.0 Delta E Requirement

ASTM F 1515 Color Resistance to Light: Meets <8.0 Delta E Requirement

Certifications: CARB II Compliant & FloorScore Certified

Country of Origin: Manufactured in China