



Durato International
 Manufacture & Trading Company
 7924 State Road
 Philadelphia, PA 19136
www.angleworld.com



2 October 2018

Description: Engineered Stone Plastic Composite with Attached IXPE Underlayment (V-EVO ® Durato™ Heavy Duty)

Warranty: Lifetime Limited Residential Wear Warranty; Lifetime Limited Structural Warranty; Lifetime Limited Waterproof Warranty; 10 Year Limited Commercial Wear Warranty

Installation: Float (5G Valinge) or Glue Down

Color: Draco

Size/Packaging: 9" x 71" x 0.374" (228*1800*9.5 mm) 17.67 sq. ft./carton, 4 planks per carton, 44 Cartons per pallet (848.16 SF)/ 18 Pallets per 40' GP

Construction: 0.5 mm/20 mil wear surface with Titan X Technology, 7 mm core (Stone & virgin DOTP Composite). 1.5 mm IXPE underlayment (No VOC)

Wear Finish: 1 coats UV-cured acrylic Gloss Level: 4% - 6%

TEST DATA

ASTM-E648 Critical Radiant Flux: Meets or exceeds, Class 1

ASTM E492-09 Impact Sound Conduction: IIC Pending (65 db)

ASTM E90-09 Airborne Sound Conduction: STC Pending (63 db)

ASTM C518 Thermal Resistance: R Value – 0.6

NALFA 3.2 Thickness Swell: Class 4, Heavy Commercial

NALFA 3.3 Xenon Light Resistance: Class 4, Heavy Commercial

NALFA 3.4 Cleanability-Stain Resistance: Class 4, Heavy Commercial

NALFA 3.5 Large Ball Impact Resistance: Class 4, Heavy Commercial

NALFA 3.6 Small Ball Impact Resistance: Class 4, Heavy Commercial

NALFA 3.8 Dimensional Tolerance: Class 4, Heavy Commercial

(0.01% @ 176°F, 400 Linear Feet install without Transitions in HVAC controlled environment)

NALFA 3.9 Caster Chair: Class 3, Commercial NALFA 3.10 Surface Bonding: 1.31 N/mm – Exceeds Class 3 Commercial Requirement

ASTM E303 Dynamic Coefficient of Friction: 0.38 DCOF (Wet slip resistance) Low Risk Classification

ASTM F-970-07 Static Load Limit: 0.001 inch – Passes at 2000 psi

ASTM-F2753 Rolling Load Over Resilient FC: Pending

ASTM F 1514 Color Resistance to Heat: Meets <8.0 Delta E Requirement

ASTM F 1515 Color Resistance to Light: Meets <8.0 Delta E Requirement

Certifications: FloorScore Certified and 100% Waterproof

Country of Origin: Manufactured in China

Available in Stone and Wood looks

100% Waterproof