Showroom Stock Truck Rules

- Only street legal 4x4 trucks may participate with no added equipment designed to increase horsepower, RPM's, torque, wheel speed, transmission function or traction. No dual wheel studded tires, chains or any tire not specifically intended for street use are permitted. Tires must carry a DOT number on the sidewall. No tire cutting is permitted.
- 2. Engine must be stock for the make and model of the truck entered. No visual modifications such as twin carbs or double pumpers, tunnel rams, blowers, turbos and the like are permitted. Any truck that runs down the track is not stock DON'T ENTER THIS CLASS.
- 3. Weight class must be 6200 lbs. This includes the driver and fuel. All weights must be in the bed.
- 4. The Hitch point may not be more than 26" from the ground. All hitches must be a Reese hitch. Hitch points must be stationary in all directions. No trick hitches.
- 5. Hitch must have a 3 \(^3\)4" hole and no clevis provided.
- 6. Must be stock from bumper to bumper.
- 7. Maximum 10 spring ply combinations.
- 8. Pump gas only, NO form of racing fuel.
- 9. Must be driven in, not hauled in.

Operation of Contest Rules

- 1. Each driver will draw for a pulling position at the time of registration. No registration will be permitted once the event has started.
- 2. Entry fee shall be \$25.00 per hook. Each truck may only be entered once, NO multiple drivers.
- 3. Number one truck may drop 6 positions. No other truck may drop.
- 4. Each truck driver must supply his own twisted clevis. Hole must accommodate a minimum of 3 3/4" inches across.
- 5. Any truck not in line and ready to pull when called will be immediately disqualified, and no refunds will be made.
- 6. All trucks may be required to return to the scales and reweigh at any time.
- Decisions of the track officials are final. No appeal to the fair committee will be heard or considered.

Street Legal 4X4

General Rules (used to be called open rules) 2 Classes

- A) Small Block 400Cl. and under plus .030 over bore
- B) Big Block 401C.I.May not exceed 540 C.I.
- 1. This is an open street legal 4x4 truck class open to owners of trucks that are used for the highway. If your truck is street legal and is built to the rules herein, you can enter this

Class. Your registration papers are required to prove that the truck is registered for street use. A license plate is required to be affixed to the truck. The registration and plates must match. Must have state inspection and insurance. Maximum of 3" exhaust must be behind the cab.

- 2. No dual wheels, studded tires, tire chains or any other tire not specifically intended for street use are permitted; tires must carry a D.O.T number on the sidewall.
- 3. Nothing may be added to the truck that would cause the vehicle to be unsafe.
- 4. Weight class shall be small block is 6300 lbs and 6300 for big block, this includes driver and fuel no hanging weights
- 5. The Hitch point may not be more than 26" from the ground. Hitch point must be the furthest point to the back of the truck. Must have a 3 ¾" minimum hole. Must have Reese style hitch under frame.
- 6. No Aluminum engine blocks permitted. No open headers or aftermarket heads.
- 7. Factory suspension must be in place. No solid suspensions allowed, however, bolt in rear suspension blocks are permitted. Must have a minimum of 1" inch travel.
- 8. Truck must have a stock appearance. Wheelbase must be proper for the cab being used. Vehicle must have a full factory unaltered bed in place. All beds must be able to safely contain weights or ballast and cover rear wheels and driveline.
- 9. Tire size is maximum of 35"X 12.50.

Operation Of Contest Rules

- 1. Each truck driver will draw for a pulling position at the time of registration. No registration will be permitted after the event has begun.
- 2. Entry fee shall be \$25.00 NO multiple drivers.
- 3. Each truck driver must supply their own twisted clevis, Hole must accommodate a minimum of 3 ¾" inches across and holes 1 inch apart.

Pro Street 4x4 Rules

- No dual wheels, studded tires, tire chains or any other tire not specifically intended for street use are permitted. Tires must carry a D.O.T number on the sidewall. Cut tires are allowed.
- 2. Weight class shall be 6300 lbs. This includes vehicle, driver, fuel and weights. Weights if added must be securely fastened. Loss of weight while under the green flag is the reason for disqualification. Weight brackets should be no more than 60" inches from the center of the front axle. No weight or ballast in the cab of the truck.
- 3. The Hitch point may not be 26" from the ground. The Hitch point must be the furthest point to the back of the truck. Pulling hitches are allowed.
- 4. Tires 35x12.5.
- 5. Truck must have a stock appearance; the wheel base must be proper or the cab being used. Must have a full factory bed in place. All beds must be able to safely contain weights or ballast and cover rear wheels and driveline.
- 6. No open driveline 1 ton or less.

- 7. No alcohol or nitrous.
- 8. Must have a kill switch and electric fuel pump shut off.
- 9. Must have all safety equipment in place.