



1. Complete, maintainable, anode system sized for the marine environment ensures decades of performance. Global spares availability!
2. U.L. listed, 12g wiring with insulated terminals.
3. Great looks and value added with a very finished look!
4. Premium quality, adjustable thermostat with high-limit reset. USCG Ignition Protected.
5. Incoloy sheathing prevents shorting of the electrical circuit should element operate if not submerged! Installed near bottom of tank to heat cooler water.
6. Spring loaded mechanism ensures safe installation of thermostat, galvanized for rust prevention.
7. Quality, finished look achieved by trimming inlet and outlet
8. ¾" inlet for standard plumbing systems! Installed near bottom of tank, close to element for faster recovery.
9. A.S.M.E. approved Temperature & Pressure Relief valve. Available in 75, 100, 125, and 150 PSI, all at 210F. 100 PSI standard equipped.
10. Curved outlet tube eliminates "sputtering" by removing trapped air from the top of the tank!
11. Inner tank is enameled, pressure tested to 300 PSI, and powder coated!
12. Jackets available in 316 brushed stainless steel or Gloss White powder coated Galvalum.
13. Exclusive heat exchanger allows removal for cleaning, should calcium or mineral buildup on the heat exchanger tubes occur! Enables replacement if freezing occurs in winterization.
14. Foam insulation yields excellent heat retention- as little as 1 degree C per hour heat loss.

**The ONLY Marine Water Heater with a 5 year COMPLETE warranty!**