



900 Harry S Truman Pkwy, Bay City, MI 48706 Phone: 989-684-2121

SPECIFICATIONS FOR H2000SE

MADE FROM AIRCRAFT ALUMINUM FOR REDUCED WEIGHT

AIR CAPACITY:	1900 C.F.M. HIGH SPEED 1200 C.F.M. LOW SPEED (1.9 RUNNING STATIC PRESSURE)
POWER:	110 VOLTS AT 9.4 RUNNING AMPS
MOTOR:	1.0 H.P. TWO-SPEED THERMAL PROTECTED
BLOWER: CAGE	2000 A.M.C.A. RATED CENTER FUGAL SQUIRREL
FILTERS:	1ST STAGE: 24 X 24 PRE FILTER 2ND STAGE: 24 X 24 RING PANEL 3RD STAGE; 24 X 24 HEPA FILTER
CASTERS:	HEAVY DUTY: 2 LOCKING SWIVEL, 2 RIGID
HANDLES:	4 PER UNIT
DIMENSIONS:	26" WIDTH 26" HEIGHT 33" LENGTH
INSTRUMENTATION:	MINIHELIC PRESSURE GAUGE 15 AMP PUSH BUTTON CIRCUIT BREAKER TWO SPEED ROCKER SWITCH
WEIGHT:	131 POUNDS