



900 Harry S Truman Pkwy, Bay City, MI 48706 Phone: 989-684-2121 or 1-800-237-6414

SPECIFICATIONS FOR MODEL 9100 “Turbo” 2000 + C.F.M. NEGATIVE AIR MACHINE

MADE FROM AIRCRAFT GRADE ALUMINUM FOR REDUCED WEIGHT

AIR CAPACITY:	2500 C.F.M. HIGH SPEED 2100 C.F.M. LOW SPEED (2.2 STATIC PRESSURE)
POWER:	115 VOLTS AT 15 AMPS
MOTOR:	1.75 H.P. TWO-SPEED THERMAL PROTECTED
BLOWER:	HIGH VOLUME, A.M.C.A Rated
FILTERS:	1ST STAGE: PRE FILTER 24 X 24 2ND STAGE: RING PANEL 24 X 24 X 1 3RD STAGE: H.E.P.A. FILTER 99.97%
CASTERS:	HEAVY DUTY: 2 RIGID, 2 SWIVEL
HANDLES;	HEAVY DUTY: 4 PER UNIT
DIMENSIONS:	26” WIDTH 26” LENGTH 32” LENGTH
INSTRUMENTATION:	MINIHELIC PRESSURE GAUGE PUSH BUTTON CIRCUIT BREAKER TWO SPEED ROCKER SWITCH
WEIGHT:	116 POUNDS
TESTING:	D.O.P. Tested at the factory