

MIRROR INSTALLATION TIPS:

1. Twist right handle grip back and forth while pulling away from handle bars and remove it. Loosen throttle by unscrewing small allen set screw and remove. Slide mirror clamp onto handlebar and tighten using the provided nut and threaded mirror shaft. Reinstall throttle and handle grip making sure handle grip does not touch the twist throttle as this could cause throttle to stay on during use.
2. THE LEFT SIDE MIRROR (AS IF SITTING ON SCOOTER) IS MOUNTED ON THE BRAKE LEVER AND DOES NOT REQUIRE SEPARATE CLAMP. REMOVE ALLEN BOLT FROM BRAKE LEVER AND MOUNT MIRROR IN CORRESPONDING HOLE.



Mount to brake lever



Install nut in rt. Side clamp



Mounting mirror to brake lever



Remove allen bolt with allen Wrench.



Retain nut under lever for later



Allen bolt and nut removed



With dust cap and nut above



insert mirror into brake lever.



Tighten mirror from the bottom of and then adjust angle and tightness with the top nut.

using original nut the brake lever

Right side Mounting



Twist the end grip while pulling



End grip removed



Locate the set screw on throttle



Loosen set screw and slide throttle off (you may need to loosen headlight to get off bar)



Throttle and end grip removed



Right side mirror clamp



Slide clamp threaded side down



Insert mirror and screw into threaded side of clamp.



Tighten nut & slide cover over.



Mirror mounted with throttle and end grip reinstalled. (Be sure end grip does not physically touch throttle as this could cause throttle to get stuck)