Printing date 19.11.2020 Revision: 19.11.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Metaflux 75-56 Pflege für Edelstahl, flüssig
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Techno Service GmbH

Detmolder Strasse 515

D-33605 Bielefeld Germany

+49 521 924440

www.metaflux.de

info@metaflux.de

· Further information obtainable from:

Sales Department

+49 521 92444-0

· 1.4 Emergency telephone number:

+49 70024112112 or +1 872 5888271 TSF 24h

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labelling:

Propan-2-ol

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P280* Wear eye protection / face protection.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents / container as special waste.

(Contd. on page 2)

Printing date 19.11.2020 Revision: 19.11.2020

Trade name: Metaflux 75-56 Pflege für Edelstahl, flüssig

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:  |   |         |
|--|---|---------|
| CAS: 67-63-0   | Propan-2-ol   | 50-100% |
| EINECS: 200-661-7  | <b>♦</b> Flam. Liq. 2, H225; <b>♦</b> Eye Irrit. 2, H319; STOT SE 3, H336 |         |
| Reg.nr.: 01-2119457558-25  |   |         |
| CAS: 64741-65-7  | Hydrocarbons, C11-C12, isoalcanes, < 2% aromatics                         | 3-<10%  |
| EC number: 918-167-1   | ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; Aquatic Chronic 4,             |         |
| Reg.nr.: 01-2119472146-39  |   |         |
| Regulation (EC) No 648/2004 on detergents / Labelling for contents |   |         |

| · Regulation (EC) No 648/2004 on detergents / Labelling for contents |          |  |
|--|----------|--|
| aliphatic hydrocarbons   | 15 - 30% |  |
| non-ionic surfactants  | < 5%     |  |
| perfumes (LIMONENE)  |          |  |

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 3)

Printing date19.11.2020 Revision: 19.11.2020

Trade name: Metaflux 75-56 Pflege für Edelstahl, flüssig

(Contd. of page 2)

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage: 3
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

| · Ingredien | Ingredients with limit values that require monitoring at the workplace:                          |                       |  |
|-------------|--|-----------------------|--|
| 67-63-0 P   | 67-63-0 Propan-2-ol  |                       |  |
| WEL (Gre    | WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm<br>Long-term value: 999 mg/m³, 400 ppm |                       |  |
| · DNELs     | · DNELs  |                       |  |
| 67-63-0 P   | ropan-2-ol   |                       |  |
| Oral        | DNEL General Population / Allgemeinheit  | 6 mg/kg BW/ day (.)   |  |
| Dermal      | DNEL Workers/Arbeiter  | 888 mg/kg BW /day (.) |  |
|             | DNEL - General Population /Allgemeinheit   | 319 mg/kg BW /day (.) |  |
| Inhalative  |  |                       |  |
|             | DNEL General Population / Allgemeinheit  | 89 mg /m3 (.)         |  |
|             | DNEL Workers / Arbeiter  | 500 mg /m3 (.)        |  |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 4)

(Contd. of page 3)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.11.2020 Revision: 19.11.2020

Trade name: Metaflux 75-56 Pflege für Edelstahl, flüssig

#### · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



· Appearance:

Tightly sealed goggles

#### SECTION 9: Physical and chemical properties

| · 9.1 Information on | basic physical ar | nd chemical properties |
|----------------------|-------------------|------------------------|
| · General Informatio | n                 |                        |

Form:
Colour:
Odour:
Odour threshold:
pH-value:

Colourless Characteristic Not determined.

Not determined.

Fluid

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 82 °C

82 °C initial boiling point

· Flash point: 13 °C

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 425 °C
• Decomposition temperature: Not determ

Decomposition temperature: Not determined.
 Self-igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 5)

Printing date 19.11.2020 Revision: 19.11.2020

Trade name: Metaflux 75-56 Pflege für Edelstahl, flüssig

|                                       |  | (Contd. of page |
|---------------------------------------|--|-----------------|
| · Explosion limits:                   |  |                 |
| Lower:                                | 2.0 Vol %                                  |                 |
| Upper:                                | 12.0 Vol %                                 |                 |
| · Vapour pressure:                    | Not determined.                            |                 |
| · Pressure (20 °C)                    | nicht bestimmt bar                         |                 |
| · Density at 20 °C:                   | 0.798 g/cm³                                |                 |
| Relative density                      | Not determined.                            |                 |
| · Vapour density                      | Not determined.                            |                 |
| · Evaporation rate                    | Not determined.                            |                 |
| · Solubility in / Miscibility with    |  |                 |
| water:                                | Not miscible or difficult to mix.          |                 |
| · Partition coefficient (n-octanol/wa | ter): Not determined.                      |                 |
| · Viscosity:                          |  |                 |
| Dynamic:                              | Not determined.                            |                 |
| Kinematic at 20 °C:                   | 10 s (DIN 53211/4)                         |                 |
| · Solvent content:                    |  |                 |
| Organic solvents:                     | ca. 86 %                                   |                 |
| VOC (EC)                              | 85.90 %                                    |                 |
| 9.2 Other information                 | No further relevant information available. |                 |
| · Additional information              | Vapors are heavier than air.               |                 |

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50  | · LD/LC50 values relevant for classification:                |                      |  |
|------------|--|----------------------|--|
| 67-63-0 Pi | 67-63-0 Propan-2-ol  |                      |  |
| Oral       | LD50   | 5045 mg/kg (rat)     |  |
| Dermal     | LD50   | 12800 mg/kg (rabbit) |  |
| Inhalative | LC50/4 h   | 30 mg/l (rat)        |  |
| 64741-65-  | 64741-65-7 Hydrocarbons, C11-C12, isoalcanes, < 2% aromatics |                      |  |
| Oral       | LD50   | >5000 mg/kg (rat)    |  |
| Inhalative | LC50/4 h   | 5 mg/l (rat)         |  |

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 19.11.2020 Revision: 19.11.2020

Trade name: Metaflux 75-56 Pflege für Edelstahl, flüssig

(Contd. of page 5)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

#### 64741-65-7 Hydrocarbons, C11-C12, isoalcanes, < 2% aromatics

|EC50| > 1000 mg/kg (fis)|

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

empty cans: material recycling

filled cans: remove in accordance with local regulations

Hand over to hazardous waste disposers.

| · European waste catalogue |  |  |
|----------------------------|--|--|
| 07 00 00                   | WASTES FROM ORGANIC CHEMICAL PROCESSES   |  |
| 07 06 00                   | wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics |  |
| 07 06 04*                  | other organic solvents, washing liquids and mother liquors                           |  |

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport information |
|-----------------------------------|
|-----------------------------------|

| · 14.1 UN-Number<br>· ADR, IMDG, IATA | UN1219                               |
|---------------------------------------|--------------------------------------|
| · 14.2 UN proper shipping name        |                                      |
| $\cdot ADR$                           | 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) |
| · IMDG                                | ISOPROPANOL (ISOPROPYL ALCOHOL)      |
| · IATA                                | Isopropanol                          |

(Contd. on page 7)

Printing date 19.11.2020 Revision: 19.11.2020

Trade name: Metaflux 75-56 Pflege für Edelstahl, flüssig

|   | (Contd. of pag  |
|---|---|
| 14.3 Transport hazard class(es)   |   |
| · ADR   |   |
|   |   |
| Class<br>Label  | 3 (F1) Flammable liquids.   |
| IMDG, IATA  |   |
|   |   |
| Class   | 3 Flammable liquids.  |
| Label   | 3   |
| 14.4 Packing group<br>ADR, IMDG, IATA   | II  |
| 14.5 Environmental hazards:<br>Marine pollutant:  | No  |
| 14.6 Special precautions for user<br>Danger code (Kemler):<br>EMS Number:<br>Stowage Category | Warning: Flammable liquids.<br>33<br>F-E,S-D<br>B   |
| 14.7 Transport in bulk according to Anne  | ex II of  |
| Marpol and the IBC Code   | Not applicable.   |
| Transport/Additional information:   |   |
| ADR Limited quantities (LQ) Excepted quantities (EQ)  | 1L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| Transport category Tunnel restriction code  | Maximum net quantity per outer packaging. 500 mt<br>2<br>D/E  |
| IMDG Limited quantities (LQ) Excepted quantities (EQ)   | 1L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| UN "Model Regulation":  | UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3,   |

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

(Contd. on page 8)

Printing date 19.11.2020 Revision: 19.11.2020

Trade name: Metaflux 75-56 Pflege für Edelstahl, flüssig

(Contd. of page 7)

| Class | Share in % |
|-------|------------|
| NK    | 76.0       |

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H413 May cause long lasting harmful effects to aquatic life.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

\* \* Data compared to the previous version altered.

GB