

# Quantum 6200 Hyperscale Security Gateway for Maestro



Check Point Maestro brings scale, agility and elasticity of the cloud on premise with efficient N+1 clustering based on Check Point HyperSync technology, maximizing the capabilities of your existing security gateways. Create your own virtualized private-cloud premise by stacking multiple Check Point security gateways together. Group them by security feature set, policy or the assets they protect and further virtualize them with virtual systems technology. With the Maestro Hyperscale Orchestrator and 6200 Hyperscale security gateways, businesses of all sizes can have cloud-level security on premise.



## Highest Security Effectiveness

Integrated with R80 and ThreatCloud to set a new standard of prevention against advanced 5<sup>th</sup> generation cyber attacks



## State-of-the-Art SSL Inspection

Threat Prevention that delivers lightning fast SSL-encrypted traffic inspection without compromising up time or scalability



## 90 Gbps of Gen V Performance

Hyperscale ready, high performance threat prevention hardware for the fastest Gen V security gateway in the industry

## PERFORMANCE HIGHLIGHTS

Gen II Security	Gen III Security	Gen V Security
Firewall	NGFW <sup>1</sup>	Threat Prevention + SandBlast <sup>2</sup>
9 Gbps	3.72 Gbps	1.8 Gbps

Performance measured with enterprise testing conditions. Additional performance details on page 3. 1: Includes Firewall, Application Control, and IPS. 2: Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection

## HIGH PERFORMANCE, SCALABLE SECURITY

### 6200 SECURITY GATEWAY




- |                                       |                               |
|---------------------------------------|-------------------------------|
| 1. Sync 10/100/1000 Base-T port       | 6. 2x USB 3.0 ports           |
| 2. RJ45 console port                  | 7. Lights-out Management port |
| 3. 1 network expansion slot           | 8. USB Type-C console port    |
| 4. 8x 10/100/1000 Base-T ports        | 9. Redundant power supplies   |
| 5. Management 10/100/1000 Base-T port |                               |

### Hyperscale Security System

With Maestro, you can start with two gateways and then can grow to up to 52 gateways. For example, when you start with 3.6 Gbps using two 6200HS gateways you can finish with a 90 Gbps security solution. Simply by using Check Point Maestro.

### Hyperscale Orchestrator Connections

When a Security Group is created, an IP address is created for a Single Management Object connection to the security management server. Easily create and assign IP addresses to the internal and external network interfaces. These uplinks are the visible components of the Maestro security solution.



### Fully Operational within Minutes

When we add a gateway to the system, it gets all the configurations, the policy, even the software version, updated and aligned with the existing deployment, ready to go within 6 minutes.

### Maestro Traffic Distribution

HyperSync tracks the Active/Standby/Backup state of group members. Sync traffic is limited to only the Active and Standby members handling the connection.

### Cost-Efficient N+1 Deployments

Now businesses of all sizes can enjoy cloud-level resiliency and telco-grade technology using the efficient Maestro N+1 clustering design.

## SPECIFICATIONS

### Performance

#### Enterprise Test Conditions

Threat Prevention (Gbps) <sup>1</sup>	1.8
NGFW (Gbps) <sup>2</sup>	3.72
IPS (Gbps)	4.65
Firewall (Gbps)	9

#### RFC 3511, 2544, 2647, 1242 PERFORMANCE (LAB)

Firewall 1518B UDP (Gbps)	17.55
VPN AES-128 (Gbps)	2.57
Connections/sec	67,000
Concurrent connections	2/4/8M

1. Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection with logging enabled. 2. Includes Firewall, Application Control and IPS with logging enabled.

### Additional Features

#### Highlights

- 4x 10 GbE SFP+ ports
- 1x CPU, 2 physical cores, 4 virtual cores
- 1x 240 GB SSD
- 2x AC power supplies
- 16 GB memory

### Content Security

#### First Time Prevention Capabilities

- CPU-level, OS-level and static file analysis
- File disarm and reconstruction via Threat Extraction
- Average emulation time for unknown files that require full sandbox evaluation is under 100 seconds
- Maximal file size for Emulation is 100 MB
- Emulation OS Support: Windows XP, 7, 8.1, 10

#### Applications

- Use 8,000+ pre-defined or customize your own applications
- Accept, prevent, schedule, and apply traffic-shaping

#### Data Loss Prevention

- Classify 700+ pre-defined data types
- End user and data owner incident handling

#### Dynamic User-based Policy

- Integrates with Microsoft AD, LDAP, RADIUS, Cisco pxGrid, Terminal Servers and with 3<sup>rd</sup> parties via a Web API
- Enforce consistent policy for local and remote users on Windows, macOS, Linux, Android and Apple iOS platforms

### Network

#### Network Connectivity

- Total physical and virtual (VLAN) interfaces per appliance: 1024/4096 (single gateway/with virtual systems)
- 802.3ad passive and active link aggregation
- Layer 2 (transparent) and Layer 3 (routing) mode

#### High Availability

- Active/Active L2, Active/Passive L2 and L3
- Session failover for routing change, device and link failure

#### IPv6

- NAT66
- CoreXL, SecureXL

#### Unicast and Multicast Routing (see SK98226)

- OSPFv2, BGP, RIP
- Static routes, Multicast routes
- Policy-based routing
- PIM-SM, PIM-DM, IGMP v2, and v3

### Maestro

#### Maximums

- Up to 8 Security Groups
- Up to 31 gateways in a Security Group
- Up to 24 gateways in a Security Group (dual site deployment, 14 from each site)
- 48x 10 GbE and 8x 100 GbE ports (MHO 140)

### Physical

#### Power Requirements

- Single Power Supply rating: 150W/300W
- AC power input: 100 to 240V (50-60Hz)
- Power consumption max: 122W
- Maximum thermal output: 416.3 BTU/hr.

#### Dimensions

- Enclosure: 1RU
- Dimensions (WxDxH): 17.2 x 20 x 1.73 in. (438 x 508 x 44mm)
- Weight: 16.5 lbs. (7.5 kg)

#### Environmental Conditions

- Operating: 0° to 40°C, humidity 5% to 95%
- Storage: -20° to 70°C, humidity 5% to 95% at 60°C

#### Certifications

- Safety: UL, CB, CE, TUV GS
- Emissions: FCC, CE, VCCI, RCM/C-Tick
- Environmental: RoHS, WEEE, REACH<sup>1</sup>, ISO14001<sup>1</sup> factory certificate

## ORDERING QUANTUM 6200HS MAESTRO SOLUTIONS

MAESTRO HYPERSCALE SOLUTION PACKAGES	SKU
Maestro Solution with two 6200 firewalls with SandBlast subscription package for 1 year and one Orchestrator (MHO-140). Each appliance includes 16 GB RAM, 10x 1GbE copper on-board, 4x 10GbE fiber, 2x AC PSUs, 1x 240 GB SSD, LOM, plus 2x 10G DAC cables (1m, 3m). MHO-140 includes 1x 10G DAC (3m).	CPAP-MHS-6202-PLUS-SNBT
Maestro Solution with three 6200 firewalls with SandBlast subscription package for 1 year and one Orchestrator (MHO-140). Each appliance includes 16 GB RAM, 10x 1GbE copper on-board, 4x 10GbE fiber, 2x AC PSUs, 1x 240 GB SSD, LOM, 2x 10G DAC cables (1m, 3m). MHO-140 includes 1x 10G DAC (3m).	CPAP-MHS-6203-PLUS-SNBT
SECURITY GATEWAY APPLIANCES FOR SCALE-UP	SKU
6200 security gateway for Maestro including 16 GB RAM, 10x 1GbE copper on-board, 4x 10GbE fiber, 2x AC PSUs, 1x 240 GB SSD, LOM, 2x 10G DAC cables (1m, 3m) with SandBlast subscription package for 1 year.	CPAP-SG6200-PLUS-MHS-SNBT

MAESTRO HYPERSCALE ORCHESTRATORS	SKU
Maestro Hyperscale Orchestrator 140 with 8x 100 GbE and 48x 10 GbE ports, plus 1x 10G DAC (3m).	CPAP-MHO-140
MAESTRO HYPERSCALE ORCHESTRATORS ACCESSORIES	SKU
Fan replacement for Maestro Hyperscale Orchestrator 140	CPAC-FAN-MHO140
AC power supply unit replacement for Maestro Hyperscale Orchestrator 140 and 170	CPAC-PSU-AC-MHO140/170
Rail kit for Maestro Hyperscale Orchestrators 140 and 170	CPAC-RAIL-MHO140/170

SECURITY GATEWAY ACCESSORIES	SKU
Direct Attach Copper (DAC) cables 10GbE SFP+ to SFP+, 1M	CPAC-DAC-10G-1M
Direct Attach Copper (DAC) cables 10GbE SFP+ to SFP+, 3M	CPAC-DAC-10G-3M
Memory upgrade kit from 16GB to 32GB for 6200 appliance	CPAC-RAM16GB-6200
Lights-Out Management Module	CPAC-LOM-C
Extended slide rails for 6200 Security Gateways (24" - 36")	CPAC-RAILS-EXT-6000/6200

### All-inclusive Security

	NGFW	NGTP	SNBT (SandBlast)
	Basic access control	Prevent known threats	Prevent known and zero-day attacks
Firewall	✓	✓	✓
VPN (IPsec)	✓	✓	✓
IPS	✓	✓	✓
Application Control	✓	✓	✓
Content Awareness	✓	✓	✓
URL Filtering		✓	✓
Anti-Bot		✓	✓
Anti-Virus		✓	✓
Anti-Spam		✓	✓
SandBlast Threat Emulation			✓
SandBlast Threat Extraction			✓

Each gateway requires a license for the enabled security feature. The first year purchase includes the SNBT package. Security subscription extensions, NGFW, NGTP and SNBT are available for subsequent years.