

WELCOME TO THE FUTURE OF CYBER SECURITY

# QUANTUM 6600 SECURITY GATEWAY



## Quantum Security Gateway™ Advantage

Protect larger environments

Greater resilience, faster operations

Handle more workloads

**Check Point Quantum 6600 Next Generation Firewalls** enables enterprises to deploy the industry's leading threat prevention capabilities at all points of their infrastructure, scaling security almost infinitely according to their changing business needs. It also dramatically accelerates the efficiency of their security operations. This enables enterprises to prevent and block even the most advanced attacks, before they can disrupt business.




### Always Protected against Gen V

Highest caliber prevention with unified security



### Security at Hyperscale

On-demand expansion with hyperscalability



### Efficient Operations

Cut operation management time by up to 80%

## PERFORMANCE HIGHLIGHTS


	Gen II Security Firewall	Gen III Security NGFW <sup>1</sup>	Gen V Security Threat Prevention + SandBlast <sup>2</sup>
Base, Plus	18 Gbps	6.2 Gbps	3.7 Gbps

Performance measured with enterprise testing conditions. Additional performance details on page 3. 1: Includes Firewall, Application Control, and IPS. 2: Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection.

WELCOME TO THE FUTURE OF CYBER SECURITY

## SPOTLIGHT

### 6600 SECURITY GATEWAY



- |                                       |                                      |
|---------------------------------------|--------------------------------------|
| 1. Sync 10/100/1000 Base-T port       | 6. 2x USB 3.0 ports                  |
| 2. RJ45 console port                  | 7. Lights-out Management port        |
| 3. 1 network expansion slot           | 8. USB Type-C console port           |
| 4. 8x 10/100/1000 Base-T ports        | 9. Redundant hot-swap power supplies |
| 5. Management 10/100/1000 Base-T port |                                      |

#### Prevent Known and Zero-day Threats

Check Point SandBlast Network is an evasion-resistant sandbox that provides zero-day protection from advanced and unknown threats. SandBlast Threat Extraction (CDR) ensures quick delivery of safe email and web content to users.

	NGFW	NGTP	NGTX
Firewall, VPN, Mobile Access	✓	✓	✓
Content Awareness	✓	✓	✓
Application Control	✓	✓	✓
Intrusion Prevention System	✓	✓	✓
URL Filtering		✓	✓
Antivirus and Anti-Bot		✓	✓
Threat Emulation (sandboxing)			✓
Threat Extraction (CDR)			✓


*Next Generation Firewall, Next Generation Threat Prevention and Threat Prevention + SandBlast packages*

#### Software and Support Bundles

Check Point security gateways come in three cost-effective bundles that include subscription and support. Purchase NGFW, NGTP or NGTX (sandboxing) with either direct or collaborative premium support for 1, 3 or 5 years.

#### High Performance Options

Purchase the affordable Plus package and get a base system plus 4x 10GbE SFP+ ports with transceivers, 2x AC power supplies, Lights-out Management and 16 GB of memory for high connection capacity.



#### Remote Management and Monitoring

A Lights-Out-Management (LOM) card provides out-of-band management to remotely diagnose, start, restart and manage the appliance from a remote location.

## ENTERPRISE-GRADE PLATFORM

	1 GbE (copper)	1 GbE (fiber)	10 GbE	Memory	Redundant Power	LOM
Base model	10	0	0	8 GB	○	○
Plus model	10	0	4	16 GB	●	●
Max capacity	18	4	4	32 GB	●	●

○ optional accessory

WELCOME TO THE FUTURE OF CYBER SECURITY

## SPECIFICATIONS

### Performance

Enterprise Test Conditions	
	Base, Plus
Threat Prevention <sup>1</sup> (Gbps)	3.7
NGFW <sup>2</sup> (Gbps)	6.2
IPS (Gbps)	10.14
Firewall (Gbps)	18
RFC 3511, 2544, 2647, 1242 PERFORMANCE (LAB)	
Firewall 1518B UDP (Gbps)	32
VPN AES-128 (Gbps)	4.9
Connections/sec	116,000
Concurrent connections <sup>3</sup>	2/4/8M

1: Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast

Zero-Day Protection. 2: Includes Firewall, Application Control and IPS. 3: Performance measured with default/Plus/maximum memory.

### Additional Features

#### Highlights

- 1x CPUs, 6x physical cores
- 1x 240GB SSD storage
- 1 AC power supply (2x in Plus)
- 8, 16 and 32 GB memory options
- Lights-Out-Management (included in Plus)
- Virtual Systems (Base/Plus/max mem): 10/20/20

#### Network Expansion Slot Options (1 of 1 slots open)

- 8x 10/100/1000Base-T RJ45 port card, up to 18 ports
- 4x 1000Base-F SFP port card, up to 4 ports
- 4x 10GBase-F SFP+ port card, up to 4 ports

### Content Security

#### First Time Prevention Capabilities

- CPU-level, OS-level and static file analysis
- File disarm and reconstruction via Threat Extraction
- Average emulation time for unknown files that require full sandbox evaluation is under 100 seconds
- Maximal file size for Emulation is 100 MB
- Emulation OS Support: Windows XP, 7, 8.1, 10

#### Applications

- Use 8,000+ pre-defined or customize your own applications
- Accept, prevent, schedule, and apply traffic-shaping

#### Data Loss Prevention

- Classify 700+ pre-defined data types
- End user and data owner incident handling

### Content Security (continued)

#### Dynamic User-based Policy

- Integrates with Microsoft AD, LDAP, RADIUS, Cisco pxGrid, Terminal Servers and with 3<sup>rd</sup> parties via a Web API
- Enforce consistent policy for local and remote users on Windows, macOS, Linux, Android and Apple iOS platforms

### Network

#### Network Connectivity

- Total physical and virtual (VLAN) interfaces per appliance: 1024/4096 (single gateway/with virtual systems)
- 802.3ad passive and active link aggregation
- Layer 2 (transparent) and Layer 3 (routing) mode

#### High Availability

- Active/Active L2, Active/Passive L2 and L3
- Session failover for routing change, device and link failure
- ClusterXL or VRRP

#### IPv6

- NAT66, NAT64, NAT46
- CoreXL, SecureXL, HA with VRRPv3

#### Unicast and Multicast Routing (see SK98226)

- OSPFv2 and v3, BGP, RIP
- Static routes, Multicast routes
- Policy-based routing
- PIM-SM, PIM-SSM, PIM-DM, IGMP v2, and v3

### Physical

#### Power Requirements

- Single Power Supply rating: 300W
- AC power input: 100 to 240V (50-60Hz)
- Power consumption max: 126W
- Maximum thermal output: 429.9 BTU/hr.

#### Dimensions

- Enclosure: 1RU
- Dimensions (WxDxH): 17.2 x 20 x 1.73 in.(438 x 508 x 44mm)
- Weight (Base/Plus): 16.5/17.4 lbs. (7.5/7.9 kg)

#### Environmental Conditions

- Operating: 0° to 40°C, humidity 95%
- Storage: -20° to 70°C, humidity 95%

#### Certifications

- Safety: UL, CB, CE, TUV GS
- Emissions: FCC, CE, VCCI, RCM/C-Tick
- Environmental: RoHS, WEEE, REACH<sup>1</sup>, ISO14001<sup>1</sup>

<sup>1</sup>. factory certificate

WELCOME TO THE FUTURE OF CYBER SECURITY

## ORDERING QUANTUM 6600 SECURITY GATEWAYS

BASE CONFIGURATION <sup>1</sup>	SKU
6600 Security Gateway Base Configuration, includes 10x1GbE copper ports, 8GB RAM, 1 SSD, 1 AC PSU	CPAP-SG6600
6600 Security Gateway Plus Configuration, includes 10x1GbE copper ports, 4x 10GbE SFP+ ports, 4x SFP+ SR transceivers, 16GB RAM, 1 SSD, 2x AC PSU, Lights-out Management	CPAP-SG6600-PLUS

<sup>1</sup> 1, 3 and 5 year NGFW, NGTP and SandBlast (NGTX) packages with Direct Premium support are available in the online product catalog.

### Accessories

INTERFACE CARDS AND TRANSCEIVERS	
8 Port 10/100/1000 Base-T RJ45 interface card	CPAC-8-1C-C
4 Port 1000Base-F SFP interface card; requires additional 1000Base SFP transceivers	CPAC-4-1F-C
SFP transceiver module for 1G fiber ports - long range (1000Base-LX)	CPAC-TR-1LX-C
SFP transceiver module for 1G fiber ports - short range (1000Base-SX)	CPAC-TR-1SX-C
SFP transceiver to 1000 Base-T RJ45 (Copper)	CPAC-TR-1T-C
4 Port 10GBase-F SFP+ interface card	CPAC-4-10F-C
SFP+ transceiver module for 10G fiber ports - long range (10GBase-LR)	CPAC-TR-10LR-C
SFP+ transceiver module for 10G fiber ports - short range (10GBase-SR)	CPAC-TR-10SR-C
MEMORY	SKU
Memory upgrade kit from 8GB to 16GB for 6600 appliance	CPAC-RAM8GB-6600
Memory upgrade kit from 8GB to 32GB for 6600 appliance	CPAC-RAM24GB-6600
Memory upgrade kit from 16GB to 32GB for 6600 appliance	CPAC-RAM16GB-6600
SPARES AND MISCELLANEOUS	SKU
Additional/Replacement AC Power Supply for 6600 and 6900 appliances	CPAC-PSU-6600/6900
Lights Out Management module	CPAC-LOM-C
Slide rails for 6000 Appliances (22" - 32")	CPAC-RAILS-6000
Extended slide rails for 6000 Appliances (24" - 36")	CPAC-RAILS-EXT-6000

Virtual Systems packages also available in the online product catalog