

# Outdoor COB Series



**Outdoor COB series are available at 1.56 mm and 1.98 mm pixel pitch with a brightness of 3000 nits and a contrast ration of 10000:1.**


**The outdoor COB series bring a fresh air to the rental and staging markets. Day or night, they offer stunning image quality in both dimmed and high brightness modes, which makes them a perfect solution for both indoor and outdoor applications.**

**Powered by the COB technology, they are of waterproof, dust-proof, anti-crash, anti-corrosion and anti-static design, very easy to install and maintain.**


**Furthermore, the outdoor COB series are an energy-saving solution, max. 170 W/pc or 680 W/m<sup>2</sup>, driven by common cathode energy-saving technology.**

# 1, Features

## 1.1, Edge-protecting design



## 1.2, Equipped with magnetic pins, easy to install



## 1.3, Detachable slave controller, no tool is needed



## 2, Specifications

<b>Model No.</b>	<b>OCS1.56</b>	<b>OCS1.98</b>
<b>Pixel pitch</b>	<b>1.56 mm</b>	<b>1.98 mm</b>
<b>Resolution</b>	<b>320 x 320</b>	<b>252 x 252</b>
<b>LED type</b>	<b>Flip COB</b>	
<b>IP rating</b>	<b>IP 65</b>	
<b>Brightness</b>	<b>3000 nits</b>	
<b>Contrast ratio</b>	<b>10000:1</b>	
<b>Max. power consumption</b>	<b>170 W/pc; 680 W/m<sup>2</sup></b>	
<b>Dimensions</b>	<b>500*500*88 mm; 19.69*19.69*3.5 inch (W*H*D)</b>	
<b>Weight</b>	<b>9.5 kg (21 lb)/pc</b>	
<b>Serviceability</b>	<b>Front/rear</b>	
<b>Refresh rate</b>	<b>3840/7680 Hz</b>	
<b>Color depth</b>	<b>14/16 Bit</b>	
<b>Viewing angle</b>	<b>Horizontal 170°; Vertical 170°</b>	
<b>LED lifetime</b>	<b>100,000 hrs (50% brightness)</b>	
<b>Operational temperature</b>	<b>-20℃～50℃ / -4°F ~ 122°F</b>	
<b>Operational humidity</b>	<b>10%～80% RH</b>	
<b>Input voltage</b>	<b>100～240V/50～60Hz</b>	
<b>Warranty</b>	<b>3 years</b>	

**Note: Specifications are subjected to change without prior notice.**