

Outdoor COB Touring

Model A



Our outdoor COB touring LED displays bring a fresh air to the rental and staging markets. Day or night, they offer stunning image quality in both dimmed and high brightness modes, which makes them a perfect solution for both indoor and outdoor applications.

Powered by the COB technology, they are of waterproof, dust-proof, anti-collision and anti-static design, very easy to install and maintain.

The outdoor COB series are available at 1.25 mm, 1.56 mm, 1.95 mm and 2.6 mm with a brightness of 4000 nits and a contrast ration of 10000:1.

Specifications

Model No.	OCT1.25A	OCT1.56A	OCT1.95A	OCT2.6A
Pixel pitch	1.25 mm	1.56 mm	1.95 mm	2.6 mm
Resolution	400 x 400	320 x 320	256 x 256	192 x 192
Pixel density	640,000 pixels/m ²	409,600 pixels/m ²	262,144 pixels/m ²	147,456 pixels/m ²
LED type	Full flip COB			
Brightness	4000 nits			
Contrast ratio	10000:1			
Power consumption	Max. 140/pc; 560 W/m ²			
IP rating	IP65			
Serviceability	Front			
Refresh rate	7680 Hz			
Color depth	16 Bit			
Viewing angle	Horizontal 170°; Vertical 170°			
LED lifetime	100,000 hrs (50% brightness)			
Operational temperature	-20°C ~ 50°C / -4°F ~ 122°F			
Operational humidity	10% ~ 85% RH			
Input voltage	100 ~ 240V / 50 ~ 60Hz			
Dimensions	500*500*88 mm; 19.69*19.69*3.5 inch (W*H*D)			
Weight	8 kg (17.64 lb)/pc; 32 kg (70.55 lb)/m ²			
Warranty	3 years			

Note: Specifications are subjected to change without prior notice.