



## Certificate of Conformity

All products meet following technical requirements

**Product: AL7525 Aluminum Surface PCB Drilling Backup Board**

Thickness:	2.5 mm
Thickness tolerance:	$\pm 0.1$ mm
Size tolerance:	$\pm 3.0$ mm
Warpage:	$< 0.5\%$ of diagonal
Surface Hardness:	Shore-D $\geq 75$ (90%)
Appearance:	Grey Surface, no dent or any other defect.
Guarantee period:	1 year

Producer: CHINA • Rizhao Norco New Material Technology Co., Ltd.

Date of manufactured: \_\_\_\_\_

Specification: \_\_\_\_\_

Quantity: \_\_\_\_\_

Number of packages: \_\_\_\_\_

**CHINA • Rizhao Norco New Material Technology Co., Ltd.**

**Signature:** \_\_\_\_\_

Supplier Reminder:

1. Protect moisture proof packing from damage, otherwise goods will absorb moisture and have deformation.
2. Products should be stored in a place of low humidity, proper storage conditions: temperature under  $25^{\circ}\text{C}$ , relative humidity 40-65%.
3. Do not open moisture proof packing in advance and exposure products. Only remove moisture proof packing until using time.
4. Packing unused products immediately with moisture proof packing and protecting cover to protect from absorbing moisture.