

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number 06100
Trade name PT Water Stop Mortar
Version 2 (EN)
Revision date 01.09.2020
Print date 13.10.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

PT Water Stop Mortar

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

The product is intended for professional users. Building products.

Uses advised against

No identified use.

1.3 Details of the supplier of the safety data sheet

Supplier / Importer

proof-tec GmbH
Wiesedermeerer Hauptstr. 24
26446 Friedeburg
GERMANY
Telephone: +49-4948-3269990
Telefax: +49-4948-3269999
E-mail: info@proof-tec.com

1.4 Emergency telephone number

+49-4948-3269990 (during business hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin corrosion/irritation

Category 2 H315

Serious eye damage/eye irritation

Category 1 H318

Specific target organ toxicity - single exposure

Category 3 H335

Full text of H- and EUH-phrases: see sec. 16.

2.2 Labelling elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

Hazard components for labelling

Cement, portland, chemicals

Calcium sulfoaluminate clinker

Signal word: Danger

Hazard pictograms



Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number 06100
Trade name PT Water Stop Mortar
Version 2 (EN)
Revision date 01.09.2020
Print date 13.10.2020

Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
Full text of H- and EUH-phrases: see sec. 16.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

Reacts strongly alkaline with water. Protect skin and eyes.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

CAS No.	EC No.	Substance name	Concentration
65997-15-1	266-043-4	Cement, portland, chemicals REACH No.: 02-2119682167-31 Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Dam. 1; H318; STOT SE 3, H335	< 20%
65997-15-1	934-133-9	Calcium sulfoaluminate clinker REACH No.: 02-2119682167-31 Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Dam. 1; H318; STOT SE 3, H335	< 15%

Full text of H- and EUH-phrases: see sec. 16.

Additional information

Products containing cement, low chromate according to Regulation 1907/2006/EC, Annex XVII (47). Attachment of the hazard warning H317 not necessary due to < 2 ppm chromium VI.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If medical advice is required, have the packaging, identification label or safety data sheet ready.

Following inhalation

Move person to fresh air, keep warm, allow to rest. Medical attention required in case of breathing difficulties.

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

Following skin contact

Wash off immediately with plenty of water and soap. Consult a doctor if symptoms persist.

Following eye contact

Immediately rinse the eyes with running water for 10 to 15 minutes with the eyelid held wide open. Remove any contact lenses if possible. Rinse further. Consult an ophthalmologist.

Following ingestion

Do not induce vomiting. Rinse mouth thoroughly with water. Allow plenty of water to be drunk in small sips (dilution effect). Call a doctor immediately.

Self-protection of the first aider

Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

After inhalation: irritation of the respiratory tract - cough; after skin contact: prolonged or repeated contact with skin or mucous membrane leads to irritation symptoms such as redness, blistering, skin inflammation etc.; after eye contact: Risk of serious damage to the eyes.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatical treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), foam or powder extinguisher, continuous water spray.

Unsuitable extinguishing media

High volume water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

No information available.

5.3 Advice for fire-fighters

In case of fire fighting respiratory protection with independent air supply and tightly fitting chemical protection suit required.

Additional information

Precipitate gases/vapours/mists with water spray jet. Collect contaminated extinguishing water separately. Do not discharge into drains or watercourses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

For emergency responders

Ensure adequate ventilation. Avoid dust formation. Use personal protective equipment. Do not inhale dust. Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

Avoid contact with water. Do not allow to enter water, sewage or soil.

6.3 Methods and material for containment and cleaning up

Avoid dust formation. Pick up mechanically. Ensure adequate ventilation. Handle the collected material in accordance with the sec. on disposal. Thoroughly clean dirty objects and floor in accordance with environmental regulations.

6.4 Reference to other sections

For advice on safe handling: see sec. 7.

For advice on protective measures: see sec. 8.

For advice on disposal: see sec. 13.

SECTION 7: Handling and storage

7.1 Protective measures for safe handling

Advice on safe handling

Use only in well-ventilated areas. Avoid dust formation. Do not inhale dust. Avoid contact with eyes and skin.

Fire preventions

No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Ensure adequate ventilation and spot extraction at critical points.

Hints on storage assembly

Keep away from food and feed.

Storage temperature for personal safety

5 - 25 °C

Further information on storage conditions

Protect against moisture. In case of moisture ingress or overlay, the contained chromate reducer may lose its effectiveness and a sensitization by skin contact cannot be excluded.

7.3 Specific end uses

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number 06100
Trade name PT Water Stop Mortar
Version 2 (EN)
Revision date 01.09.2020
Print date 13.10.2020

CAS No.	Substance	Value	Peak limit	Type
65997-15-1	Cement, portland, chemicals	10 mg/m ³ E 1,25 mg/m ³ A	2 (II)	AGW (DE)
65997-15-1	Calcium sulfoaluminate clinker	10 mg/m ³ E 1,25 mg/m ³ A	2 (II)	AGW (DE)
471-34-1	Calcium carbonate	10 mg/m ³ E 1,25 mg/m ³ A 6 mg/m ³ A	2 (II)	AGW (DE)

A: alveolar fraction, E: respirable fraction

DNEL/DMEL-values - DNEL Worker

CAS No./DNEL type

471-34-1

Long-term – inhalation, local effects

7778-18-9

Acute – inhalation, systemic effects

Long-term – inhalation, systemic effects

Substance/Value

Calcium carbonate

4,26 mg/m³

Calcium sulfate

5,082 mg/m³

21,17 mg/m³

DNEL/DMEL-values - DNEL Consumer

CAS No./DNEL type

471-34-1

Long-term – inhalation, local effects

7778-18-9

Long-term – oral, systemic effects

Acute – inhalation, systemic effects

Long-term – inhalation, systemic effects

Substance/Value

Calcium carbonate

1,06 mg/m³

Calcium sulfate

1,52 mg/kg KG/d

3,811 mg/m³

5,29 mg/m³

PNEC

CAS No./PNEC type

471-34-1

Sewage treatment plant

7778-18-9

Sewage treatment plant

Substance/Value

Calcium carbonate

100 mg/l

Calcium sulfate

100 mg/l

8.2 Exposure controls

Appropriate engineering controls

In open handling, devices with local exhaust ventilation must be used. Do not inhale dust.

Personal protective equipment

General protection and hygiene measures

Immediately remove all soiled, soaked clothing. Draw up and observe skin protection plan! Wash hands and face thoroughly before breaks and at the end of work. Do not eat, drink, smoke or snort at the workplace.

Eye / Face protection

Basket glasses according to EN 166.

Skin protection

Wear suitable protective clothing during work.

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

Hand protection

Protective gloves according to EN 374, nitrile rubber (NBR). Breakthrough time (maximum wearing time): >480 min.
The manufacturer's specifications for permeability and breakthrough times must be observed.

Respiratory protection

Respiratory protection is required in case of insufficient ventilation. Particle filter unit (DIN EN 143) with particle filter - type P2 (medium separation efficiency - identification colour: white) or particle filter - type P3 (high separation efficiency - identification colour: white). For short-term use: dust protection mask.

Environmental exposure controls

This substance must not be disposed of in the sewerage system, in soil or in water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	solid
Colour:	grey
Odour:	characteristic
pH:	11 - 13,5
Melting point/freezing point:	> 1.000 °C
Relative density:	0,9 - 1,5 g/cm ³ at 20 °C
Solubility(ies):	reacts with water

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Product cures with moisture.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Reacts strongly alkaline with water.

10.4 Conditions to avoid

Moisture, water

10.5 Incompatible materials

Strong acids, strong alkalis, base metals, strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products when stored and handled correctly.

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Details on Cement, portland, chemicals

Acute toxicity, oral

Result: No acute oral toxicity was found in animal studies with cement kiln dusts and cement dusts.

Acute toxicity, dermal

Dose: LD50 2.000 mg/kg

Species: Rabbit

Duration: 24 h

Result: No lethality.

Acute toxicity, inhalative

Dose: LD50 5 g/m³

Species: Rat

Result: No acute toxicity.

Skin corrosion/irritation

Result: Has a skin and mucous membrane irritating effect.

Eye damage/irritation

Result: Risk of serious eye damage and blindness.

Sensitisation to the respiratory tract/skin

Sensitisation to the respiratory tract

Result: Based on the available data, the classification criteria are not met.

Skin sensitisation

Result: Irritant or allergic contact dermatitis possible.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Result: Based on the available data, the classification criteria are not met.

Carcinogenicity

Result: Based on the available data, the classification criteria are not met.

Reproductive toxicity

Result: Based on the available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Result: May cause irritation of the respiratory tract and mucous membranes.

Specific target organ toxicity (repeated exposure)

Result: Based on the available data, the classification criteria are not met.

Aspiration hazard

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

Result: Based on the available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Following skin contact:	May cause irritation.
Following inhalation:	May cause irritation.
Following eye contact:	May cause serious eye damage.

Details on Calcium sulfoaluminate clinker

Acute toxicity, oral

Result: No acute oral toxicity was found in animal studies with cement kiln dusts and cement dusts.

Acute toxicity, dermal

Dose:	LD50 2.000 mg/kg
Species:	Rabbit
Duration:	24 h
Result:	No lethality.

Acute toxicity, inhalative

Dose:	LD50 5 g/m ³
Species:	Rat
Result:	No acute toxicity.

Skin corrosion/irritation

Result: Has a skin and mucous membrane irritating effect.

Eye damage/irritation

Result: Risk of serious eye damage and blindness.

Sensitisation to the respiratory tract/skin

Sensitisation to the respiratory tract

Result: Based on the available data, the classification criteria are not met.

Skin sensitisation

Result: Irritant or allergic contact dermatitis possible.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Result: Based on the available data, the classification criteria are not met.

Carcinogenicity

Result: Based on the available data, the classification criteria are not met.

Reproductive toxicity

Result: Based on the available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Result: May cause irritation of the respiratory tract and mucous membranes.

Specific target organ toxicity (repeated exposure)

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

Result: Based on the available data, the classification criteria are not met.

Aspiration hazard

Result: Based on the available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Following skin contact:	May cause irritation.
Following inhalation:	May cause irritation.
Following eye contact:	May cause serious eye damage.

Details on Calcium sulfate

Sensitisation to the respiratory tract/skin

Sensitisation to the respiratory tract

Result: Based on the available data, the classification criteria are not met.

Skin sensitisation

Result: Based on the available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Result: Based on the available data, the classification criteria are not met.

Carcinogenicity

Result: Based on the available data, the classification criteria are not met.

Reproductive toxicity

Result: Based on the available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Result: Based on the available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Result: Based on the available data, the classification criteria are not met.

Aspiration hazard

Result: Based on the available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Following skin contact:	May cause irritation.
Following eye contact:	May cause serious eye damage.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Details on Cement, portland, chemicals

No data available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

Details on Calcium sulfoaluminate clinker

No data available.

Details on Calcium carbonate

No data available.

Details on Calcium sulfate

Acute (short-term) fish toxicity

Dose:	LC50 > 10.000 mg/l
Duration:	96 h
Species:	Oncorhynchus mykiss (rainbow trout)

Acute (short-term) toxicity to crustacea

Dose:	EC50 > 1.000 mg/l
Duration:	48 h
Species:	Daphnia magna (big water flea)

Acute (short-term) toxicity to algae and cyanobacteria

Dose:	EC50 > 200 mg/l
Species:	Daphnia magna (big water flea)

12.2 Persistence and degradability

Details on Cement, portland, chemicals

The product is not easily biodegradable.

Details on Calcium sulfoaluminate clinker

The product is not easily biodegradable.

Details on Calcium carbonate

No data available.

Details on Calcium sulfate

No data available.

12.3 Bioaccumulative potential

Details on Cement, portland, chemicals

No data available.

Details on Calcium sulfoaluminate clinker

No data available.

Details on Calcium carbonate

No data available.

Details on Calcium sulfate

No data available.

12.4 Mobility in soil

Details on Cement, portland, chemicals

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

No data available.

Details on Calcium sulfoaluminate clinker

No data available.

Details on Calcium carbonate

No data available.

Details on Calcium sulfate

No data available.

12.5 Results of PBT and vPvB assessment

The mixture does not meet the criteria for classification as PBT or vPvB.

12.6 Other adverse effects

No data available.

Additional ecotoxicological information

Do not allow undiluted or large quantities to enter the sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose in accordance with applicable international, national and local laws, ordinances and statutes. When mixed with Component A and fully reacted/cured can be disposed of in landfill. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used. Non-contaminated and completely empty packaging can be recycled. Contaminated packaging must be treated as the substance.

SECTION 14: Transport information

14.1 Landtransport (ADR/RID)

No dangerous good in sense of these transport regulations.

14.2 Inland waterway transport (ADN)

No dangerous good in sense of these transport regulations.

14.3 Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

14.4 Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH)

Item number	06100
Trade name	PT Water Stop Mortar
Version	2 (EN)
Revision date	01.09.2020
Print date	13.10.2020

Authorisations and/or restrictions on use

This product contains one or more substances that are subject to authorisation: Port-land cement (chromium VI reduced), CAS No. 65997-15-1, Item 47

National regulations

Notes on employment restrictions

Observe employment restrictions for young people (§ 22 JArbSchG). Observe employment restrictions for expectant and nursing mothers.

15.2 Chemical Safety Assessment

Chemical safety assessments have been carried out by the respective REACH registrants for substances > 10 t/a. No assessment has been carried out for the present mixture.

SECTION 16: Other information

16.5 Text of the hazard statements and/or safety instructions referred to in sec.s 2 to 15

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

16.7 Further information

To the best of our knowledge, the information in this safety data sheet is correct at the time of printing. The information is intended to provide guidelines for the safe handling of the product mentioned in this safety data sheet during storage, processing, transport and disposal. The information is not transferable to other products. Insofar as the product is mixed, blended or processed with other materials, the information in this safety data sheet cannot be transferred to the new material manufactured in this way, unless expressly stated otherwise. The information is based on our current state of knowledge, but does not constitute a guarantee of product properties and does not establish a contractual legal relationship. Existing laws and regulations must be observed by the recipient of our products on his own responsibility.